

Appendix E: Precast R-Value Calculations

The next analysis that was performed was the **Steady State Isothermal Analysis Method #1:**

Using a series-parallel method of calculation, Isothermal Analysis predicts the effects of irregular sized and spaced penetrations through an insulation layer. Individually, steel or concrete have significant effects on the insulation layer and can be predicted with this analysis method.

The Isothermal Analysis by itself has been proven a bit aggressive when figuring the effects of solid concrete sections and therefore has been tempered with U-Value average to account for the restricted conduction zones affected by solid concrete.

The steady state thermal analysis shows the total isothermal R-value for the wall, with the ability to factor in thermal breaks such as metal ties or solid concrete sections.

You will notice in the findings shown in the Isothermal Analysis that the THERMOMASS wall panel has a material R-Value of **R-11.49**. The Isothermal Analysis shows **.90%** thermal loss in this wall panel with the use of fiber composite connectors. The overall material R-Value of the THERMOMASS wall consists of an **R-11.39**.

The competing wall system which consists of 2X4 steel studs (16" oc), 2" XPS insulation, full exterior brick w/ brick ties connected back to the steel studs. Due to the thermal conductivity of the brick ties this assumed R-11.66 wall actually performs at an **R-7.76** (33% reduction).

Steady-State Thermal Analysis by Modified Isothermal Analysis Method


Study Provided For:

Penta Career Center - Perrysburg, OH
3"/2"/5" TM vs. 2x4 steel stud 2"XPS & brick (pt 1)



DESIGN INFORMATION FOR WALL PANELS

SYSTEM CRITERIA	THERMOMASS® SPEC.	PANEL DESIGN #2
Insulation Type	EXTRUDED	EXTRUDED
Connector Type	FIBER-COMP	BRICK TIE
Connector Conductivity	6.9	365.0
Connector Area	13.50 in ²	15.12 in ²
Net Wall Area	43,200 in ² 300.00 ft ²	43,200 in ² 300.00 ft ²
Insulation Conductivity	0.20	0.20
Concrete Conductivity	12.50	12.50
Solid Concrete Area	0.00 in ²	0.00 in ²
R-value of Air Film Coefficients	0.85	0.85

WALL CONFIGURATION:	LAYERS	COVER:	LAYERS	COVER:
 <ul style="list-style-type: none"> • Ext. Conc. Wythe: • Insulation: • Int. Conc. Wythe: 	3.00 in.	1.00 in.	10.00 in.	5.00 in.
	2.00 in.		2.00 in.	
	5.00 in.	3.00 in.	0.10 in.	0.10 in.

ASSUMPTIONS: All values for extruded insulation based on ASTM C-578 specifications for Type IV - extruded polystyrene insulation @ base temperature of 75°F. -Part 1 of 2 - Value for brick veneer calculated to equal 10 inches of concrete.

This Modified "Isothermal Planes" Method combines Series-Parallel Path Analysis, ASHRAE Handbook - 2001 Fundamentals, Chapter 23 and U-value Average Analysis as validated through CTC/DOE Thermal Study 1999.

CALCULATED RESULTS SUMMARY


	THERMOMASS® SPEC.			PANEL DESIGN #2				
	R VALUE		LOSS	R VALUE			% of LOSS	
	Assumed	Isothermal	%	Assumed	Isothermal	Modified	To Iso.	To Mod.
1.00 in.	6.49	6.44	0.80%	6.66	4.71	4.71	29.32%	29.32%
1.50 in.	8.99	8.91	0.86%	9.16	6.23	6.23	31.95%	31.95%
2.00 in.	11.49	11.39	0.90%	11.66	7.76	7.76	33.46%	33.46%
3.00 in.	16.49	16.33	0.94%	16.66	10.81	10.81	35.11%	35.11%
4.00 in.	21.49	21.28	0.96%	21.66	13.86	13.86	36.00%	36.00%
5.00 in.	26.49	26.23	0.98%	26.66	16.91	16.91	36.56%	36.56%
6.00 in.	31.49	31.18	0.99%	31.66	19.96	19.96	36.94%	36.94%
7.00 in.	36.49	36.13	0.99%	36.66	23.02	23.02	37.21%	37.21%
8.00 in.	41.49	41.08	1.00%	41.66	26.07	26.07	37.42%	37.42%

Composite Technologies Corporation believes the information and recommendations herein to be accurate and reliable. However, since use conditions are not within its control, Composite Technologies Corporation does not guarantee results from use of such products or other information herein and disclaims all liability for any resulting damage or loss. No warranty expressed or implied is given as to the merchantability, fitness for particular purpose, or otherwise with respect to the product referred to. Freedom from patents of THERMOMASS®, the THERMOMASS® Building System or others is not to be inferred. NOTICE: STYROFOAM brand insulation will burn and should be handled and installed properly. For proper use, consult applicable building code requirements, fire regulations, and specific instructions in literature available from your supplier or The Dow Chemical Company, Midland MI 48674.

Property of Composite Technologies Corporation. Any unauthorized use is subject to litigation.

©2004 Composite Technologies Corporation

9:45 PM, 12/30/2008



Performance Mass Analysis:

A precast concrete sandwich wall panel system constructed with The THERMOMASS Insulation System maximizes the thermal mass effect of concrete, thereby reducing the heating and cooling loads and providing an R-Value greater than what can be expected by the material alone (R-11.49) or by which code requires.

When utilizing climate data for Perrysburg, OH the proposed 3-in exterior concrete / 2-in extruded polystyrene insulation / 5-in interior concrete THERMOMASS Wall Panel performs at **R-20.64**.

This is determined by taking into account climate data, building orientation, occupancy type, and facility type. ASHRAE/IESNA Standard 90.1-1989: System Performance Criteria is the standard calculation used.

This criteria determines the R-Value performance and the heating and cooling load adjustments for the effects of concrete mass within the building envelope. The results of the analysis are detailed in image to the right.

ASHRAE 90.1-2001 Compliant Building Envelope Performance Study

Study Provided For:

Penta Career Center - Perrysburg, OH

3"/2"/5" THERMOMASS - Edge to edge XPS insulation



SYSTEM PERFORMANCE CRITERIA		MASS ANALYSIS 1.2																																																																
The result of the balanced equation comparison of the designed, high-mass concrete wall to the similarly designed, non-mass wall is a relationship of energy performance in Btu's to R-value. Note: The material wall R-value is not altered by the dynamics of the building and the climate. The performance value represented below is a portrayal of energy consumption as a function of insulation performance.																																																																		
PERFORMANCE STUDY SUMMARY																																																																		
THERMOMASS BUILDING	<table border="1"> <thead> <tr> <th></th> <th>North</th> <th>East</th> <th>South</th> <th>West</th> </tr> </thead> <tbody> <tr> <td colspan="5">COOLING LOAD FOR DESIGNED WALL</td> </tr> <tr> <td>WCc</td> <td>3.003577</td> <td>2.946804</td> <td>3.344073</td> <td>2.766502</td> </tr> <tr> <td>WCt</td> <td>12.060956</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Btu Consumption</td> <td>12,060,956</td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="5">HEATING LOAD FOR DESIGNED WALL</td> </tr> <tr> <td>WCh</td> <td>4.397850</td> <td>4.244893</td> <td>3.820091</td> <td>4.215030</td> </tr> <tr> <td>WCt</td> <td>16.677863</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Btu Consumption</td> <td>16,677,863</td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="5">TOTAL ESTIMATED LOAD</td> </tr> <tr> <td>WCt</td> <td>28.739</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Btu Consumption</td> <td>28,738,819</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>					North	East	South	West	COOLING LOAD FOR DESIGNED WALL					WCc	3.003577	2.946804	3.344073	2.766502	WCt	12.060956				Btu Consumption	12,060,956				HEATING LOAD FOR DESIGNED WALL					WCh	4.397850	4.244893	3.820091	4.215030	WCt	16.677863				Btu Consumption	16,677,863				TOTAL ESTIMATED LOAD					WCt	28.739				Btu Consumption	28,738,819				STEADY-STATE WALL R-value:	11.49
		North	East	South	West																																																													
	COOLING LOAD FOR DESIGNED WALL																																																																	
	WCc	3.003577	2.946804	3.344073	2.766502																																																													
	WCt	12.060956																																																																
	Btu Consumption	12,060,956																																																																
	HEATING LOAD FOR DESIGNED WALL																																																																	
	WCh	4.397850	4.244893	3.820091	4.215030																																																													
	WCt	16.677863																																																																
	Btu Consumption	16,677,863																																																																
TOTAL ESTIMATED LOAD																																																																		
WCt	28.739																																																																	
Btu Consumption	28,738,819																																																																	
					STEADY-STATE WALL U-value:	0.087																																																												
					WALL HEAT CAPACITY	20.00																																																												

LOW-MASS BUILDING	<table border="1"> <thead> <tr> <th></th> <th>North</th> <th>East</th> <th>South</th> <th>West</th> </tr> </thead> <tbody> <tr> <td colspan="5">COOLING LOAD FOR DESIGNED WALL</td> </tr> <tr> <td>WCc</td> <td>3.587098</td> <td>3.498771</td> <td>3.994383</td> <td>3.467419</td> </tr> <tr> <td>WCt</td> <td>14.547671</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Btu Consumption</td> <td>14,547,671</td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="5">HEATING LOAD FOR DESIGNED WALL</td> </tr> <tr> <td>WCh</td> <td>3.708222</td> <td>3.572308</td> <td>3.333991</td> <td>3.576626</td> </tr> <tr> <td>WCt</td> <td>14.191148</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Btu Consumption</td> <td>14,191,148</td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="5">TOTAL ESTIMATED LOAD</td> </tr> <tr> <td>WCt</td> <td>28.739</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Btu Consumption</td> <td>28,738,819</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>					North	East	South	West	COOLING LOAD FOR DESIGNED WALL					WCc	3.587098	3.498771	3.994383	3.467419	WCt	14.547671				Btu Consumption	14,547,671				HEATING LOAD FOR DESIGNED WALL					WCh	3.708222	3.572308	3.333991	3.576626	WCt	14.191148				Btu Consumption	14,191,148				TOTAL ESTIMATED LOAD					WCt	28.739				Btu Consumption	28,738,819				STEADY-STATE WALL R-value:	20.64
		North	East	South	West																																																													
	COOLING LOAD FOR DESIGNED WALL																																																																	
	WCc	3.587098	3.498771	3.994383	3.467419																																																													
	WCt	14.547671																																																																
	Btu Consumption	14,547,671																																																																
	HEATING LOAD FOR DESIGNED WALL																																																																	
	WCh	3.708222	3.572308	3.333991	3.576626																																																													
	WCt	14.191148																																																																
	Btu Consumption	14,191,148																																																																
TOTAL ESTIMATED LOAD																																																																		
WCt	28.739																																																																	
Btu Consumption	28,738,819																																																																	
					STEADY-STATE WALL U-value:	0.05																																																												
					WALL HEAT CAPACITY	1.00																																																												

THIS THERMAL MASS, ANALYTICAL COMPARISON RESULTS IN THE THERMOMASS WALL BEHAVING AS A WALL WITH A MATERIAL R-VALUE OF: 20.64

Composite Technologies Corporation believes the information and recommendations herein to be accurate and reliable. However, since use conditions are not within its control, Composite Technologies Corporation does not guarantee results from use of such products or other information herein and disclaims all liability for any resulting damage or loss. No warranty expressed or implied is given as to the merchantability, fitness for particular purpose, or otherwise with respect to the product referred to. Freedom from patents of THERMOMASS®, the THERMOMASS® Building System or others is not to be inferred. NOTICE: STYROFOAM brand insulation will burn and should be handled and installed properly. For proper use, consult applicable building code requirements, fire regulations, and specific instructions in literature available from your supplier or The Dow Chemical Company, Midland MI 48674.

