



ARCHITECTURAL ENGINEERING

CONSTRUCTION MANAGEMENT

SENIOR THESIS

APRIL 11th, 2011

CONSULTANT: DR. RILEY





ARCHITECTURAL ENGINEERING
CONSTRUCTION MANAGEMENT
SENIOR THESIS
APRIL 11TH, 2011
CONSULTANT: DR. RILEY

PRESENTATION OUTLINE

- I. PROJECT OVERVIEW
- II. Project Team
- III. Overview of Analyses
- IV. ANALYSIS 1 LEED CERTIFICATION
- V. Analysis 2 Brick Façade
- VI. MECHANICAL BREADTH
- VII. Analysis 3 BIM Coordination
- VIII.CONCLUSION
- IX. ACKNOWLEDGEMENTS
- X. Questions





I. PROJECT OVERVIEW

II. PROJECT TEAM

III. OVERVIEW OF ANALYSES

IV. Analysis 1 – Leed Certification

V. Analysis 2 – Brick Façade

VI. MECHANICAL BREADTH

VII. Analysis 3 – BIM Coordination

VIII. CONCLUSION

IX. ACKNOWLEDGMENTS

X. QUESTIONS

PROJECT OVERVIEW

Project Title: Paint Branch High School

FUNCTION: EDUCATION

Location: Burtonsville, MD

BUILDING SIZE: 349,000 SF

PROJECT COST: \$ 80,973,293

DATE OF CONSTRUCTION: 12/15/2009 – JULY 30, 2013

Delivery Method: Modified CM @ Risk





PRESENTATION OUTLINE:

- I. PROJECT OVERVIEW
- II. PROJECT TEAM
- III. OVERVIEW OF ANALYSES
- IV. Analysis 1 Leed Certification
- V. Analysis 2 Brick Façade
- VI. MECHANICAL BREADTH
- VII. Analysis 3 BIM Coordination
- VIII. CONCLUSION
- IX. ACKNOWLEDGMENTS
- X. QUESTIONS

PROJECT OVERVIEW

PHASE 1:

- CONSTRUCTION OF THE NEW FACILITY
- Substantial completion date: June 1, 2012


PHASE 2:

- Reconfigure Parking Lots for Staff & Students
- SUBSTANTIAL COMPLETION DATE: AUGUST 19, 2011

PHASE 3:

- ABATEMENT & DEMOLITION OF OLD FACILITY
- SUBSTANTIAL COMPLETION DATE: JULY 30, 2013

PB PHASE DIAGRAM





- I. PROJECT OVERVIEW
- II. PROJECT TEAM
- III. OVERVIEW OF ANALYSES
- IV. Analysis 1 Leed Certification
- V. Analysis 2 Brick Façade
- VI. MECHANICAL BREADTH
- VII. Analysis 3 BIM Coordination
- VIII. CONCLUSION
- IX. ACKNOWLEDGMENTS
- X. QUESTIONS

PROJECT TEAM

Owner: Montgomery County Public

SCHOOLS (MCPS)

ARCHITECT: MOSELEY ARCHITECTS

CONSTRUCTION MANAGER: HESS CONSTRUCTION + ENGINEERING

SERVICES

CIVIL ENGINEER ADTEK ENGINEERS

MEP ENGINEER: B2E CONSULTING ENGINEERS

STRUCTURAL ENGINEERS: WOLFMAN & ASSOCIATES

PROJECT TEAM













- I. PROJECT OVERVIEW
- II. PROJECT TEAM
- III. OVERVIEW OF ANALYSES
- IV. Analysis 1 LEED Certification
- V. Analysis 2 Brick Façade
- VI. MECHANICAL BREADTH
- VII. Analysis 3 BIM Coordination
- VIII. CONCLUSION
- IX. ACKNOWLEDGEMENTS
- X. QUESTIONS

OVERVIEW OF ANALYSES

ANALYSIS 1: LEED CERTIFICATION

- REVIEWING LEED SCORECARD FOR OPPORTUNITIES
- ANALYZING OPPORTUNITIES FOR ADDITIONAL COSTS

Analysis 2: Brick Façade

- COST & SCHEDULE IMPACT TO PROJECT
- MECHANICAL BREADTH
- STRUCTURAL BREADTH

ANALYSIS 3: BIM COORDINATION

- REVIEWING CLASH DETECTION LOGS AND CASE STUDIES
- DETERMINE COST AND SCHEDULE SAVINGS TO PROJECT





- I. PROJECT OVERVIEW
- II. PROJECT TEAM
- III. OVERVIEW OF ANALYSES
- IV. ANALYSIS 1 LEED CERTIFICATION
- V. Analysis 2 Brick Façade
- VI. MECHANICAL BREADTH
- VII. Analysis 3 BIM Coordination
- VIII. CONCLUSION
- IX. ACKNOWLEDGEMENTS
- X. QUESTIONS

ANALYSIS 1 – LEED CERTIFICATION

PROBLEM:

- STATE OF THE ART HIGH SCHOOL
- LEED GOLD CERTIFIED (43 POINTS)

RESEARCH GOALS/METHODOLOGY:

- REVIEW LEED SCORECARD FOR OPPORTUNITIES
- ACHIEVE LEED PLATINUM CERTIFICATION (52 POINTS)



LEED VERSION 2.2

GREEN SCHOOLS STATISTICS

DAYLIGHT:

- WITH BRIGHTER LEARNING ENVIRONMENTS, TEST SCORES INCREASE BY 25%
- ABILITY TO LEARN 20-25% FASTER ON STANDARDIZED TESTS

AIR QUALITY:

- CHILDREN MISS 10 MILLION SCHOOL DAYS A YEAR DUE TO ASTHMA
- POOR AIR QUALITY CAN CAUSE MOLD GROWTH AND DISEASE TO SPREAD

ACOUSTICS:

- STUDENTS SCORE UP TO 20% HIGHER ON WORD RECOGNITION TESTS
- POOR ACOUSTICS CAUSE DISTRACTION, WHICH AFFECTS A STUDENTS ABILITY TO LEARN


DIAB SHETAYHI

Architectural Engineering Spring 2011 – Senior Thesis



- I. PROJECT OVERVIEW
- II. PROJECT TEAM
- III. OVERVIEW OF ANALYSES
- IV. ANALYSIS 1 LEED CERTIFICATION
- V. Analysis 2 Brick Façade
- VI. MECHANICAL BREADTH
- VII. Analysis 3 BIM Coordination
- VIII. CONCLUSION
- IX. ACKNOWLEDGEMENTS
- X. QUESTIONS

LEED SCORECARD



SUSTAINABLE SITES

- Credit 7.1 Heat Island Effect, Non-Roof
 - Placed 50% of parking under canopy

ENERGY & ATMOSPHERE

- CREDIT 2.1 ON-SITE RENEWABLE ENERGY
 - INCORPORATED WIND TURBINE ON SITE
- CREDIT 4 ENHANCED REFRIGERANT MANAGEMENT
 - CHANGED REFRIGERANT TO R134A
- Credit 5 Measurement & Verification
 - THIRD PARTY TO ESTABLISH PLAN

INDOOR ENVIRONMENTAL QUALITY

- CREDIT 1 OUTDOOR AIR DELIVERY MONITORING
 - Incorporated CO2 monitoring Systems
- CREDIT 5 INDOOR CHEMICAL & POLLUTANT SOURCE CONTROL
 - PROPOSED ENTRY GRATES AT ALL MAJOR ENTRANCES
- Credit 7.1 Thermal Comfort, Design
 - HEATING & COOLING LOADS TO BE CALCULATED BY ME



I. PROJECT OVERVIEW

II. PROJECT TEAM

III. OVERVIEW OF ANALYSES

IV. ANALYSIS 1 – LEED CERTIFICATION

V. Analysis 2 – Brick Façade

VI. MECHANICAL BREADTH

VII. Analysis 3 – BIM Coordination

VIII. CONCLUSION

IX. ACKNOWLEDGEMENTS

X. QUESTIONS

CREDIT 7.1 – HEAT ISLAND EFFECT, NON-ROOF

REQUIREMENTS:


- 50% of parking spaces under deck/roof
- Material used must have a Solar Reflectance Index (SRI)² of at least 29

TOTAL PARKING SPACES: 355

TOTAL PARKING SPACES REQUIRED: 178

TOTAL PARKING SPACES UNDER CANOPY: 188





- = SINGLE CANTILEVER SYSTEM
- = Double Cantilever System

Diab Shetayhi

Architectural Engineering Spring 2011 – Senior Thesis




- I. PROJECT OVERVIEW
- II. PROJECT TEAM
- III. OVERVIEW OF ANALYSES
- IV. ANALYSIS 1 LEED CERTIFICATION
- V. Analysis 2 Brick Façade
- VI. MECHANICAL BREADTH
- VII. Analysis 3 BIM Coordination
- VIII. CONCLUSION
- IX. ACKNOWLEDGEMENTS
- X. Questions

CREDIT 7.1 – COST ANALYSIS

| Cost Analysis | | | | | |
|-------------------|---------------------|-----------------|---------|------------|--|
| Canopy System | Total Parking Spots | Total Linear Ft | Cost/LF | Total Cost | |
| Single Cantilever | 47 | 470 | \$300 | \$ 141,000 | |
| Double Cantilever | 141 | 780 | \$600 | \$ 468,000 | |
| Total | 188 | 1,250 | \$900 | \$ 609,000 | |





- = SINGLE CANTILEVER SYSTEM
- = DOUBLE CANTILEVER SYSTEM



- I. Project Overview
- II. PROJECT TEAM
- III. OVERVIEW OF ANALYSES
- IV. ANALYSIS 1 LEED CERTIFICATION
- V. Analysis 2 Brick Façade
- VI. MECHANICAL BREADTH
- VII. ANALYSIS 3 BIM COORDINATION
- VIII. CONCLUSION
- IX. ACKNOWLEDGEMENTS
- X. QUESTIONS

COMPLETE COST ANALYSIS

| LEED Cost Analysis | | | |
|------------------------------|--|--------|-----------|
| | | | |
| Sustainable Sites | | Points | Cost |
| Credit 7.1 | Heat Island Effect, Non Roof | 1 | \$609,000 |
| | | | |
| Energy & Atmosphere | | Points | Cost |
| Credit 2.1 | On-Site Renewable Energy | 1-3 | \$25,000 |
| Credit 4 | Enhanced Refrigerant Management | 1 | N/A |
| Credit 5 | Measurement & Verification | 1 | \$55,000 |
| | | | |
| Indoor Environmental Quality | | Points | Cost |
| Credit 1 | Outdoor Air Delivery Monitoring | 1 | \$123,200 |
| Credit 5 | Indoor Chemical & Pollutant Source Control | 1 | \$156,695 |
| Credit 7.1 | Thermal Comfort, Design | 1 | N/A |
| | Total Possible Points/Cost | 9 | \$968,859 |

ANALYSIS 1 CONCLUSION

ADVANTAGES:

- SAVINGS IN OPERATING COSTS
- INCREASED TEST SCORES
- CLEANER LEARNING ENVIRONMENT

DISADVANTAGES:

• HIGH UPFRONT COST

Diab Shetayh



- I. PROJECT OVERVIEW
- II. PROJECT TEAM
- III. Overview of Analyses
- IV. Analysis 1 Leed Certification
- V. Analysis 2 Brick Façade
- VI. MECHANICAL BREADTH
- VII. Analysis 3 BIM Coordination
- VIII. CONCLUSION
- IX. ACKNOWLEDGEMENTS
- X. QUESTIONS


ANALYSIS 2 – BRICK FAÇADE

PROBLEM:

- CONGESTED SITE
- FAÇADE IS PRIMARILY FACE BRICK


RESEARCH GOALS/METHODOLOGY:

- CONTACTING PREFAB. MANUFACTURERS
- DETERMINE COST & SCHEDULE IMPACT WITH NEW SYSTEM



CURRENT SYSTEM:

- 4" FACE BRICK
- 1" AIR SPACE
- 2" RIGID INSULATION
- 10" CMU



PROPOSED SYSTEM:

- 1" face Brick
- 3.5" Polyurethane
- 4" STEEL STUD
- 5/8" Gypsum Board
- 1" MEMBRANE (2)
- ½" FIBERBOARD

Diab Shetayh



- I. PROJECT OVERVIEW
- II. PROJECT TEAM
- III. Overview of Analyses
- IV. Analysis 1 Leed Certification
- V. Analysis 2 Brick Façade
- VI. MECHANICAL BREADTH
- VII. ANALYSIS 3 BIM COORDINATION
- VIII. CONCLUSION
- IX. ACKNOWLEDGEMENTS
- X. QUESTIONS


CALCULATIONS

TOTAL SF OF BRICK: 108,000 SF

PREFAB. PANEL SIZE: 12' X 40' = **480 SF**


TOTAL NUMBER OF PANELS NEEDED: 225 PANELS

Panels Installed Per Day: 8-15 panels (5 man crew)



CURRENT SYSTEM:

- 4" FACE BRICK
- 1" AIR SPACE
- 2" RIGID INSULATION
- 10" CMU



PROPOSED SYSTEM:

- 1" FACE BRICK
- 3.5" Polyurethane
- 4" STEEL STUD
- 5/8" Gypsum Board
- 1" MEMBRANE (2)
- ½" FIBERBOARD



- I. Project Overview
- II. PROJECT TEAM
- III. OVERVIEW OF ANALYSES
- IV. Analysis 1 Leed Certification
- V. Analysis 2 Brick Façade
- VI. MECHANICAL BREADTH
- VII. Analysis 3 BIM Coordination
- VIII. CONCLUSION
- IX. ACKNOWLEDGEMENTS
- X. Questions

FAÇADE COMPARISON

| Masonry Systems Comparison | | | | | |
|------------------------------|----------------|----------------------|-------------------|--|--|
| Original Masonry System | | | | | |
| <u>Duration</u> | Cost/SF | SF of Brick | <u>Total Cost</u> | | |
| 139 Days | \$20.62 | 108,000 \$2,226,960. | | | |
| | | | | | |
| Prefabricated Masonry Panels | | | | | |
| <u>Duration</u> | <u>Cost/SF</u> | <u>SF of Brick</u> | <u>Total Cost</u> | | |
| 19 days | \$40.00 | 108,000 | \$4,320,000.00 | | |

SCHEDULE SAVINGS: 139 DAYS – 19 DAYS = 120 DAYS (6 MONTHS)

ADDITIONAL COST: \$4,320,000 - \$2,226,960 = \$2,093,040

ANALYSIS 2 CONCLUSION

ADVANTAGES:

- DECREASE IN PROJECT SCHEDULE
- MINIMIZE SITE CONGESTION
- BETTER QUALITY

DISADVANTAGES:

• MORE EXPENSIVE SYSTEM

Diab Shetayh



- I. PROJECT OVERVIEW
- II. PROJECT TEAM
- III. OVERVIEW OF ANALYSES
- IV. ANALYSIS 1 LEED CERTIFICATION
- V. Analysis 2 Brick Façade
- VI. MECHANICAL BREADTH
- VII. Analysis 3 BIM Coordination
- VIII. CONCLUSION
- IX. ACKNOWLEDGEMENTS
- X. QUESTIONS

MECHANICAL BREADTH

COMPARISON IN R –VALUES AND U-VALUES

CALCULATE EACH SYSTEMS HEAT TRANSFER

CONDUCT COST ANALYSIS BETWEEN BOTH SYSTEMS


CURRENT SYSTEM:

- 4" FACE BRICK
- 1" AIR SPACE
- 2" RIGID INSULATION
- 10" CMU


PROPOSED SYSTEM:

- 1" face Brick
- 3.5" Polyurethane
- 4" STEEL STUD
- 5/8" GYPSUM BOARD
- 1" Membrane (2)
- ½" FIBERBOARD

WALL SECTIONS



Current System



PROPOSED SYSTEM



I. Project Overview

II. PROJECT TEAM

III. Overview of Analyses

IV. Analysis 1 – Leed Certification

V. Analysis 2 – Brick Façade

VI. MECHANICAL BREADTH

VII. ANALYSIS 3 – BIM COORDINATION

VIII. CONCLUSION

IX. ACKNOWLEDGEMENTS

X. QUESTIONS

CURRENT FAÇADE

| R & U Values (Brick Façade) | | | | |
|-----------------------------|--------------------|---------------|-------------|--|
| Material | Material Thickness | R-value/inch | R-value | |
| Air Film | 1" | 1.00 | 1.00 | |
| Brick | 4" | 0.011 | 0.44 | |
| CMU | 10" | 1.20 | 12.00 | |
| nsulation | 2" | 4.00 | 8.00 | |
| | | Total R-value | 21.44 | |
| | | U-Value (1/R) | 0.046641791 | |

PROPOSED FAÇADE

| R & U Values (Prefabricated System) | | | | | |
|-------------------------------------|--|---|--|--|--|
| Material Thickness | R-value/inch | R-value | | | |
| 1" | 0.11 | 0.011 | | | |
| 3.5" | 6.25 | 21.875 | | | |
| 4" | 1.38 | 5.52 | | | |
| 0.625" | 0.56 | 0.35 | | | |
| 0.08" | 1.00 | 0.16 | | | |
| 0.5" | 1.32 | 0.66 | | | |
| | Total R-values | 28.576 | | | |
| | U-Value (1/R) | 0.034994401 | | | |
| | Material Thickness 1" 3.5" 4" 0.625" 0.08" | Material ThicknessR-value/inch1"0.113.5"6.254"1.380.625"0.560.08"1.000.5"1.32Total R-values | | | |



- I. PROJECT OVERVIEW
- II. PROJECT TEAM
- III. OVERVIEW OF ANALYSES
- IV. Analysis 1 Leed Certification
- V. Analysis 2 Brick Façade
- VI. MECHANICAL BREADTH
- VII. Analysis 3 BIM Coordination
- VIII. CONCLUSION
- IX. ACKNOWLEDGEMENTS
- X. QUESTIONS

COST ANALYSIS

| Cost Analysis | | | | | |
|-----------------------------------|---|--|---------------------|--|--|
| Summer: $\Delta T = 100-75 = 25F$ | | | | | |
| Brick Façade | q=0.0467*108,000*25F=126,090 BTU/h | 126,090*4,380=552,274,200 BTU/yr. | | | |
| Prefabricated Façade | q=0.0350*108,000*25F=94,150 BTU/h | 94,500*4,380=413,910,000 BTU/yr. | | | |
| | | Difference | 138,364,200 BTU/yr. | | |
| | | | 40,584.66 kWh/yr. | | |
| Cost/kWhr in MD = \$0.125kWh | | | | | |
| Winter: $\Delta T = 70-16 = 3$ | 54F | | | | |
| Brick Façade | q=0.0467*108,000*54F=272,354.4 BTU/h | 272,354.4*4,380=1,192,912,272 BTU/yr. | | | |
| Prefabricated Façade | q=0.0350*108,000*54F =204,120 BTU/h | 204,120*4,380=894,045,600 BTU/yr. | | | |
| | | Difference | 298,866,672 BTU/yr. | | |
| | | | 87,585.11 kWh/yr. | | |
| Cost/kWh in MD = \$0.125 kWh | | | | | |
| | | Total Savings per year: \$16.016.72 | | | |

COST ANALYSIS

ALTERNATIVE INTERIOR FINISH:

- CHANGED CMU FINISH TO GYPSUM WALL BOARD
- CHANGED RIGID INSULATION TO POLYURETHANE

| Gypsum Board Estimate | | | | | |
|-----------------------|---------------|---------------|------------------|--------------|--------------|
| laterial | Mat'l Cost/SF | Labor Cost/SF | Area/Panel (ft²) | Total Panels | Total Cost |
| ypsum Wall Board | \$0.48 | \$0.54 | 480 | 225 | \$109,404.00 |
| olyurethane | \$1.50 | | 480 | 225 | \$162,000.00 |
| | | | | Total= | \$271,404.00 |



- I. PROJECT OVERVIEW
- II. PROJECT TEAM
- III. Overview of Analyses
- IV. Analysis 1 Leed Certification
- V. Analysis 2 Brick Façade
- VI. MECHANICAL BREADTH
- VII. ANALYSIS 3 BIM COORDINATION
- VIII. CONCLUSION
- IX. ACKNOWLEDGEMENTS
- X. QUESTIONS

ANALYSIS 3 – BIM COORDINATION






Architectural Engineering Spring 2011 – Senior Thesis



- I. PROJECT OVERVIEW
- II. PROJECT TEAM
- III. Overview of Analyses
- IV. ANALYSIS 1 LEED CERTIFICATION
- V. Analysis 2 Brick Façade
- VI. MECHANICAL BREADTH
- VII. ANALYSIS 3 BIM COORDINATION
- VIII. CONCLUSION
- IX. ACKNOWLEDGEMENTS
- X. Questions







Architectural Engineering Spring 2011 – Senior Thesis



- I. PROJECT OVERVIEW
- II. PROJECT TEAM
- III. Overview of Analyses
- IV. Analysis 1 Leed Certification
- V. Analysis 2 Brick Façade
- VI. MECHANICAL BREADTH
- VII. ANALYSIS 3 BIM COORDINATION
- VIII. CONCLUSION
- IX. ACKNOWLEDGEMENTS
- X. Questions





Architectural Engineering Spring 2011 – Senior Thesis

Diab Shetayh



- I. PROJECT OVERVIEW
- II. PROJECT TEAM
- III. Overview of Analyses
- IV. ANALYSIS 1 LEED CERTIFICATION
- V. Analysis 2 Brick Façade
- VI. MECHANICAL BREADTH
- VII. Analysis 3 BIM Coordination

VIII. CONCLUSION

- IX. ACKNOWLEDGEMENTS
- X. QUESTIONS


CONCLUSION

ANALYSIS 1:

- ACHIEVED LEED PLATINUM CERTIFICATION
- Total Additional Cost \$968,859

ANALYSIS 2:

- Additional Cost W/ Prefab System \$2,093,040
- SAVINGS IN PROJECT SCHEDULE 6 MONTHS







- I. PROJECT OVERVIEW
- II. PROJECT TEAM
- III. OVERVIEW OF ANALYSES
- IV. ANALYSIS 1 LEED CERTIFICATION
- V. Analysis 2 Brick Façade
- VI. MECHANICAL BREADTH
- VII. Analysis 3 BIM Coordination
- VIII. CONCLUSION
- IX. ACKNOWLEDGEMENTS
- X. QUESTIONS

ACKNOWLEDGEMENTS

ACADEMIC ACKNOWLEDGEMENTS:

- Dr. Riley CM Advisor
- Dr. Robert Leicht
- Dr. John Messner
- PENN STATE AE FACULTY

Special Thanks To:

- MATT EVANS (HESS CONSTRUCTION)
- SAURABH GANGWAR (HESS CONSTRUCTION)
- GEORGE HOUKE (HESS CONSTRUCTION)
- PAINT BRANCH PROJECT TEAM

ACKNOWLEDGEMENTS













- . Project Overview
- II. PROJECT TEAM
- III. Overview of Analyses
- IV. Analysis 1 Leed Certification
- V. Analysis 2 Brick Façade
- VI. MECHANICAL BREADTH
- VII. Analysis 3 BIM Coordination
- VIII. CONCLUSION
- IX. ACKNOWLEDGEMENTS
- X. QUESTIONS

QUESTIONS?

QUESTIONS?

Architectural Engineering Spring 2011 – Senior Thesis