

Owner: Boston University  
Site: John Hancock Student Village  
Occupant: BU Student Housing  
Type: Residential  
Size: 26 stories  
396,000 total sf



### Project Team:

CM & GC: Walsh Brothers  
Architect: Cannon Design  
MEP: Cannon Design  
Structure: Weidlinger Associates  
Construction: January '07 - April '09  
Cost: \$291 Million

### Architecture:

- \* Two-tower configuration sharing a common core and lower entry levels.
- \* South Tower is 19 stories and the north tower is 26 stories.
- \* Panelized terracotta and metal panel rainscreen exterior skin system.

### Structure:

- \* Reinforced Concrete MAT foundations are 3'-9" for the shorter tower and 4'-3" for the taller tower
- \* Steel structure utilizes a braced framing system to transfer lateral loads to foundation
- \* Lightweight concrete slab on metal decking for composite floor construction



### Mechanical:

- \* A desiccant wheel energy recovery ventilation system for all suites and apartments.
- \* Evaporative coolers on the ventilation units to supplement the air-cooled DX cooling system.
- \* ECM motors and a variable flow fan coil system for each HVAC unit serving each suite and apartment.

### Electrical:

- \* Medium Voltage (13.8 kV) Service will be tied to the existing Student Housing Phase 1 BU switchgear loop extension.
- \* Total Demand with Growth Factor (1.5) is 5,226 kVA
- \* Secondary distribution voltage will be 480 V (3 phase) to provide service to equipment loads and 208 V (3 phase) for dwelling demand loads.



### Lighting:

- \* High efficiency lighting systems have been provided throughout the building. The average lighting power density is approximately 0.78W/sf, compared with the code allowed 1.5 w/sf. This has been achieved using high efficiency ballasts and luminaires