





creation.

<u>Construction</u> Jenna Dumke Jeff Sopinski		<u>Lighting/Electrical</u> Abby Kun Amanda Small	
<u>Structural</u> Patrick Zuza Emily Wychock		<u>Mechanical</u> Kristiana McMunn Mike Hoffacker	

Presentation 4: Proposal

AEI Student Competition:


Reading School District Elementary School





creation.

Results

Team Goal: To create an innovative, high-performance environment in a way that stimulates involvement in both education & the community.



Purpose & Team Goals



Results





creation.

BIM Execution Plan





BIM Uses	Applicable Software
Scheduling	P6
Clash Detection	Navisworks
Estimating	RSMMeans CostWorks
Virtual Mockups	SketchUp



BIM Uses	Applicable Software
Lighting Calculations	AGi32
Daylighting & Electrical Integration	Daysim
Wiring, Circuiting, Systems Coordination	Revit
Rendering	3ds Max



BIM Uses	Applicable Software
Systems Coordination	Revit
Gravity System	RAM
Lateral System	ETABS
Modeling Space Frames	AutoCAD
Masonry Design	RAM Element



BIM Uses	Applicable Software
Scheduling	Trace
Clash Detection	Revit
4D Modeling	Excel



creation.


Production Schedule

Milestone:	Proposal Presentation							Progress Review 1 1/9/13			Progress Review 2 1/23/13			Progress Review 3 2/6/13			Electronic Submission Deadline 2/22/13
Week:	11/12/2012	11/19/2012	11/26/2012	12/3/2012	12/10/2012	12/17/2012	12/24/2012	12/31/2012	1/7/2013	1/14/2013	1/21/2013	1/28/2013	2/4/2013	2/11/2013	2/18/2013		
School Systems Design Finalization	Green Roof Design																
	Systems Finalization																
Pool Design	Preliminary Load Calculations																
	System Design & Coordination																
	3D Review & Clash Detection																
Clinic Design	Preliminary Load Calculations																
	System Design & Coordination																
	3D Review & Clash Detection																
Report	Report Development & Finalization																

Proposal Presentation
Winter Break
Progress Review 1
Progress Review 2
Progress Review 3


creation.

Proposed Plan

Master Plan
Design Considerations

- Restricted Site
- Renovation
- Traffic Flow
- Parking Accessibility
- Geothermal Boring Location
- Constructability
- Site Lighting and Light Trespass

Our Plan




Enclosure

create a functional barrier from exterior elements while maintaining aesthetic appeal & interior comfort.

creation.

CONSTRUCTABILITY

- Two concrete wythes separated by insulation
- Lightweight = larger panel sizes, smaller structural frame
- Less crane picks, faster installation
- Local fabricator within 20 miles = fast deliveries, low delivery costs
- \$27 per SF
- \$1,102,300.00



create a functional barrier from exterior elements while maintaining aesthetic appeal & interior comfort.



Enclosure

WALL DESIGN GOALS


To achieve our target U-value, while minimizing costs and optimizing energy efficiency and constructability.

WALL DESIGN CRITERIA

ASHRAE 90.1 Required U-value = 0.069

ASHRAE 50% energy savings recommended U-value = 0.037

OUR WALL: U-Value = 0.383



creation.

FENESTRATION DESIGN GOALS

To maximize the amount of natural daylight in the classroom spaces, while minimizing the cost of construction and optimizing energy savings.

FENESTRATION DESIGN CRITERIA

ASHRAE 90.1 Requirements: U-Value = 0.55, SHGC = 0.4,

ASHRAE 50% Energy savings recommendation: U-value = 0.45, SHGC = 0.5, VT = 0.63


Window to Wall Ratio < 40%

Enclosure

create a functional barrier from exterior elements while maintaining aesthetic appeal & interior comfort.

RESULTS



Our Window: U-Value = 0.54, SHGC = 0.4, VT = 0.6
Window to Wall Ratio = 29.5%



creation.


Enclosure

create a functional barrier from exterior elements while maintaining aesthetic appeal & interior comfort.




creation.

Enclosure



create a functional barrier from exterior elements while maintaining aesthetic appeal & interior comfort.



- Panels attached to steel frame
- Bay spacing to accommodate desired window area




creation.

Enclosure Green Roof Analysis

CONSTRUCTABILITY

- Lightweight system
- Minimal maintenance
- Retains rainwater during droughts
- Open joint assembly
- Access to substrate




Green Roof Depth: 4”

Compared to a dark roof :

Electrical: 3179.2 kWh
 Total Energy Cost Savings: \$407.40

Compared to a white roof :

Electrical: 1707.7 kWh
 Total Energy Cost Savings: \$288.79



ROOF DESIGN GOALS


To achieve our target U-value, while minimizing additional structure costs and optimizing energy efficiency and constructability.

ROOF DESIGN CRITERIA

ASHRAE 90.1 U-value = 0.048 with insulation entirely above deck, c.i.
 ASHRAE 50% energy savings recommended U-value = 0.0333 with c.i

RESULTS

Our Roof: U-value = 0.0333



creation.


Enclosure Results

WALL: U-Value = 0.383
 ROOF: U-value = 0.033
 WINDOW: U-Value = 0.540, SHGC = 0.4, VT = 0.6



create a functional barrier from exterior elements while maintaining aesthetic appeal & interior comfort.

ENTIRE ENCLOSURE ENERGY SAVINGS

ENERGY USE INTENSITY



Reduced energy use intensity by 22 kBTU/ft²-yr
 (represents all selected enclosure materials with a ground source heat pump system)



creation.

Atrium

create an attractive & secure entrance to
welcome students, faculty, and guests.

creation.

Atrium

create an attractive & secure entrance to welcome students, faculty, and guests.


DESIGN CONSIDERATIONS

- Mechanical loads
 - Glass – high solar loads
 - Air must be supplied for all three floors
- Glare
- Diffuse Daylighting
- Light Levels
- Safety




creation.

Atrium

December 21st @ Noon

Average Illuminance: 25 fc

June 21st @ Noon

Average Illuminance: 53 fc

create an attractive & secure entrance to welcome students, faculty, and guests.



creation.




Classrooms

create a stimulating & comfortable learning
environment.

creation.

Classrooms

create a stimulating & comfortable learning environment.





creation.

Classrooms

create a stimulating & comfortable learning environment.

- Typical bay 28 x 30
- Limited beam depths
- Composite metal deck



creation.



Classrooms

create a stimulating & comfortable learning environment.



Masonry Shear Wall


Braced Frame



creation.



Classrooms

create a stimulating & comfortable learning environment.



Supply



Return




Classrooms

create a stimulating & comfortable learning environment.

Test Mode (Full Output)




A/V Mode




50% Light Output with Board Light

Total Classroom Energy Savings per Year: 21,000 kWh

creation.





Company	Fixture Series	Mounting	Lamp
Pinnacle	Linero 8 – 4' & 8'	Suspended	T8
Ledalite	Jump – 8'	Wall	8' LED
Ligholier	LED Micro Undercabinet	Surface	10W/LF LED



creation.


Classrooms



LIGHTOLIER
EX 2 Edge-Lit Exit Series
Double Face, Self-Powered

Equipment Type	Manufacturer	Specific Details
Television	Sony	Wall mounted, data supply for basic television and morning news
Projector	InFocus	Classroom grade projector, ceiling mounted, interactive screen functions
Computers	Dell	High performance and functionality, touchscreen interaction

** Alternate products are also acceptable if required specifications can be met **



creation.

Administration

create a productive & inviting work
environment

creation.


Administration

DESIGN CONSIDERATIONS

- Mechanical equipment noise
- Security system
- Structural grid irregularity



create a productive & inviting work environment



Company	Fixture Series	Mounting	Lamp
1. Pinnacle	Adeo 2'x2', 2'x4'	Recessed	T8
2. Lightolier	Calculite 6"x6" Square DL	Recessed	27W LED
3. Lightolier	Wal-Master Wall Washer	Recessed	T8
4. AXIS	Beam 4 – Perimeter System	Recessed	T8

2'x2' Tile Ceiling – Dropped at 8'

creation.


DESIGN CONSIDERATIONS

- Mechanical equipment noise
- Security system
- Structural grid irregularity



Administration

create a productive & inviting work environment



creation.


Administration

DESIGN CONSIDERATIONS

- Mechanical equipment noise
- Security system
- Structural grid irregularity

Visiplex System Functions

- Classroom and Building Speakers
- Intercom system at entry
- Synchronized Clocks
- Fire Alarm Announcement Integrated
- All Controlled from main admin office, as well as from an intranet log in from home computers



creation.

Corridor

create a space which accommodates traffic flow
and major building system components

Corridor

DESIGN CONSIDERATIONS


- Plenum space
- Acoustics

create a space which accommodates traffic flow
and major building system components



creation.

Corridor



Pinnacle
Linerio 8 - 8ft length

create a space which accommodates traffic flow
and major building system components

Design Criteria from IES Lighting Handbook	
Age Range	25-65
Average Illuminance	5 fc
Avg:Min Ratio	2:1

Lighting Power Density (Based on Standard 90.1)	
ASHRAE 90.1	0.66 W/SF
Actual LPD	0.25 W/SF

- Exposed ceiling
- Fixtures
 - 8ft AFF
 - Spaced 30ft on center
- Acoustic paneling
 - Hung from ceiling and mounted high on walls



creation.



Multipurpose Room

create a flexible space for the school and
community.

creation.

Multipurpose Room


create a flexible space for the school and community.



creation.

Multipurpose Room

create a flexible space for the school and community.



Fixtures

- 15 (6) 54W T5HO
- Philips Day-Brite Fluorescent Gym Luminaire

Design Criteria from IES Lighting Handbook (for Class 3 Sports Lighting)

Age Range	25-65
Average Illuminance	50 fc
Avg:Min Ratio	3:1


Lighting Power Density (Based on Standard 90.1)

ASHRAE 90.1	1.20 W/SF
Actual LPD	0.89 W/SF



creation.

Multipurpose Room




4'x4' with 2.5' light well

Passive Daylighting System
 paired with
So-Dark Motorized Shade Screen


By Daylighting Systems, Inc.

create a flexible space for the school and community.

Useful Daylight Illuminance
 (500 lux and greater)



Without Skylights



With Skylights

Energy Savings per Year =
1,791 kWh



creation.

Pool & Clinic Renovation

create a recreational building to encourage
healthy living and community involvement

creation.

Pool & Clinic Renovation


CONSTRUCTABILITY

- Scheduling & Phasing
- Site Logistics
- Budget

DESIGN CONSIDERATIONS

- Humidity
- Energy Savings
- Large roof span
- Lighting fixtures



create a recreational building to encourage healthy living and community involvement



creation.

Pool & Clinic Renovation


create a recreational building to encourage healthy living and community involvement





creation.

Pool & Clinic Renovation

create a recreational building to encourage healthy living and community involvement



Northwest corner



creation.

Pool & Clinic Renovation

create a recreational building to encourage healthy living and community involvement

Fixture Considerations


- High Bay Fixtures
- Water tight fixtures
- Complete lifecycle cost analysis



Design Criteria from IES Lighting Handbook (for Class 3 Sports Lighting)	
Age Range	25-65
Average Deck Illuminance	100 fc
Average Water Illuminance	300 fc
Avg:Min Ratio	3:1

Lighting Power Density (Based on Standard 90.1)

ASHRAE 90.1	1.20 W/SF
-------------	-----------



creation.Lighting Power DensityInterior: about **46,000 W/SF****44.8%** below ASHRAE Standard 90.1 Requirements*Does not include specialty lighting spaces (Library & Atrium)Floor to Floor Height Reduction SavingsFaçade: **6775** square feet, **\$182,000**Structural Steel: **762 LF**, **38100 lbs**, **\$50,000**Air Volume: **660,000 CF**

Team Goal: To create an innovative, high-performance environment in a way that stimulates involvement in both education & the community.

LEED CertificationCurrently **51** points for LEED SilverOperability

Decreased maintenance of green roof
Less maintenance of geothermal mechanical system

Energy Use Intensity savings

Reduced the building energy use intensity by **22** kBTU/ft²-yr through enclosure design and system selection

Building Systems

Lighting/Electrical Systems

- Public Spaces all on Building Management System
- Emergency fixtures will also serve as normal power and default to emergency when necessary.
- 277/480V Lighting Panels, 120/208V Electrical Panels
- Interior building transformer and generator
- On site High Voltage transformer; secondary
- Overhead power lines supply building

Construction

- Multiple Prime with Construction Management Agency
- Proposed CM @ Risk w/ Design Assist Subs
- Construction Budget: \$18,00,000
- 15 Month Schedule
- Rammed Aggregate Piers



Structural Systems

- Structural steel frame, typical classroom 28x30
- W10 and W12 columns spliced at 3rd floor
- W14 girders and W12 beams, W8 girders in corridors
- Braced frames and reinforced masonry shear walls
- Composite metal deck

Mechanical Systems

- Ground Source Heat Pump System
- 5 Dedicated Outdoor Air Units serving 5 zones
- Outdoor air units take the majority of the sensible and latent loads
- Ventilation and Terminal Unit split system
- Heat Pumps range in size from 3/4 – 3 tons

creation.

Images taken from:

[axislighting.com](#)

[daylighting.com](#)

[lightolier.com](#)

[ledalite.com](#)

[pinnacle-ltg.com](#)

[Lithonia.com](#)

[acoustimac.com](#)