


The New York Times

Intro

Building Background
Proposal

Façade Redesign
Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD
Metrics of Success



Project Team



BIM TEAM 3: MATT HEDRICK | KYLE HORST | CASEY LEMAN | ANDRES PEREZ

The New York Times

Intro

Building Background

Proposal

Façade Redesign


Floor System Redesign

Core Redesign


CoGen Redesign

BIM/IPD

Metrics of Success



Building Statistics



www.international-pc.com/

The New York Times Building

- o 620 Eighth Ave. Times Square
- o Midtown Manhattan, New York, NY

Building Owners

- o The New York Times Company: Floors 2 - 27
- o Forrest City Ratner Companies: Floors 29 - 50

Building Cost

- o Assumed construction cost of \$ 1 billion (2007)
- o New York Times Portion: \$ 604 - \$ 624 million

Building Function

- o Class A Office Building
- o Retail Space on Ground Floor

The New York Times

Intro

Building Background

Proposal

Façade Redesign


Floor System Redesign

Core Redesign

CoGen Redesign

BIM/IPD

Metrics of Success



Building Background

Building Architecture

- o 52 story office building, 745' tall
- o Unique façade with ceramic rod shading system
- o 1.5 million square feet

Vertical Transportation

- o 28 elevators serving the tower
- o High speed "smart" design (1,600 ft/min)
- o Cutting edge call system

Mechanical

- o 6250 ton chilled water system
- o 1.4 MW cogeneration system
- o District steam heating
- o UFAD / VAV air distribution

Lighting/Electrical

- o 18,000 Luminaires
- o Fixtures Controlled by a Digitally Addressable Lighting Interface (DALI)
- o 5 Transformers with Room for Expansion

Structural

- o Composite Beam & Girder Floor System
- o Steel Braced Frame Lateral Force Resisting System
- o Outriggers on 28th & 51st Mechanical Levels
- o Exposed Pretension Exterior Steel Rods
- o Exposed 30"x30" Built-up Steel Columns
- o Thermal Trusses on 51st Mechanical Floors



www.international-pc.com/


BIM TEAM 3: MATT HEDRICK | KYLE HORST | CASEY LEMAN | ANDRES PEREZ

The New York Times

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD
Metrics of Success



Project Team



Architects	Renzo Piano Building Workshop FXFOWLE Architects
CM	AMEC Construction Mgmt. (Core & Shell) Turner Construction (NYT Interiors)
Structural	Thornton Tomasetti
MEP	Flack and Kurtz

Project Milestones


- o August 23, 2004 – Excavation Begins
- o July 2006 – Topping Out Ceremony
- o November 19, 2007 – Grand Opening of the New York Times Building

The New York Times

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD
Metrics of Success



Redesign Goals



Increased Profitability

- Operating Costs
- Leasable Space

Increased Marketability

- Sustainability
- Iconic Image

Redesign Strategies

Decrease floor to floor height to allow for an additional rentable floor

Redesigning core to add additional rentable space on each floor


Improve the sustainability profile

The New York Times

Intro
 Building Background
Proposal

Façade Redesign
 Floor System Redesign
 Core Redesign
 CoGen Redesign

BIM/IPD
 Metrics of Success




IPD / BIM Goals



www.international-pc.com/

Integrated Project Delivery

- Building Information Modeling (BIM)
- Project Goal Setting
- BIM Use Analysis




The New York Times

Intro
Building Background
Proposal

Facade Redesign

Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD
Metrics of Success



Façade Redesign

Façade Goals:

- o Increase Thermal Efficiency
- o Maintain or Exceed Daylighting Performance
- o Maintain Iconic Image

Transparency
Lightness
Innovative Design

Redesign Opportunities:

- o Explore Double-Skin Façade
- o Explore Alternate Shading Techniques

Maintaining the Image

- o Double-Skin Façade of the London Bridge Place

Innovative
Contemporary
Sustainable

- o A Glass Tower With a Distinct Identity




The New York Times

Intro
Building Background
Proposal

Facade Redesign

Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD
Metrics of Success




System Description

2' 6" Ventilated Cavity System Using Two Skins of Glass

1" Interior Insulating Glazing Curtain Wall

5/8" Exterior Laminated Glazing Unit

Horizontal Louvered Shading System



The New York Times


- Intro
- Building Background
- Proposal

Facade Redesign


- Floor System Redesign
- Core Redesign
- CoGen Redesign

BIM/IPD


Metrics of Success



System Description





- Intro
- Building Background
- Proposal
- Facade Redesign**
- Floor System Redesign
- Core Redesign
- CoGen Redesign
- BIM/IPD
- Metrics of Success




Facade Daylight Analysis

Daylight Autonomy: Double-Skin with Louvers



Daylight Autonomy: Ceramic Rods



The New York Times


Intro
Building Background
Proposal

Facade Redesign

Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD

Metrics of Success



Façade Daylight Analysis

Single Floor Lighting Power Consumption

Maximum Potential: 71 kWh


Rod Design: 27 kWh

Louvered Design: 28 kWh

Both Designs: 60% Energy Savings



Facade Redesign



Thermal Loads

Existing HVAC Envelope Loads:


- o Peak cooling: 58%
- o Peak heating: 75%

Double-Skin Façade Thermal Efficiency:

- o Decreased U-value
- o Decreased Shading Coefficient

	Existing Façade	Double-Skin Façade
U-Value	0.625	0.50
Shading Coefficient	0.750	0.38

Facade Redesign



Thermal Loads

Existing HVAC Envelope Loads:

- o Peak cooling: 58%
- o Peak heating: 75%


Double-Skin Façade Thermal Efficiency:

- o Decreased U-value
- o Decreased Shading Coefficient


Savings:

- o Energy (21%)

Yearly Energy Consumption by Floor



Facade Redesign



Thermal Loads

Existing HVAC Envelope Loads:

- o Peak cooling: 58%
- o Peak heating: 75%


Double-Skin Façade Thermal Efficiency:

- o Decreased U-value
- o Decreased Shading Coefficient


Savings:

- o Energy (21%)
- o Cost (\$800,000 / year)

Yearly Energy Costs by Floor



Facade Redesign



Thermal Loads

Existing HVAC Envelope Loads:

- o Peak cooling: 58%
- o Peak heating: 75%


Double-Skin Façade Thermal Efficiency:

- o Decreased U-value
- o Decreased Shading Coefficient

Savings:

- o Energy (21%)
- o Cost (\$800,000 / year)
- o Emissions (23%)

HVAC Associated Emissions by Floor (CO₂e)



The New York Times


- Intro
- Building Background
- Proposal

Facade Redesign


- Floor System Redesign
- Core Redesign
- CoGen Redesign

BIM/IPD

Metrics of Success




Serviceability and Maintenance



2' 6" accessible cavity

Louvers support walking loads




The New York Times

Intro
Building Background
Proposal

Facade Redesign

Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD
Metrics of Success



Cost Comparison:

Double-skin façade up front cost: \$18.7 million increase

Annual energy savings: \$800,000

Simple payback period : 23.43 years

Original Façade System	\$ 83,527,260
Proposed Double Façade	\$ 102,273,745
Upfront Cost Increase	\$ 18,746,485
Annual Energy Savings	\$ (800,000)
Simple Payback Period	23.43 Years


The New York Times

- Intro
- Building Background
- Proposal


Facade Redesign

- Floor System Redesign
- Core Redesign
- CoGen Redesign

- BIM/IPD
- Metrics of Success




Facade Lighting Redesign



400W Floodlight



250W Floodlight



The New York Times


- Intro
- Building Background
- Proposal

Facade Redesign




- Floor System Redesign
- Core Redesign
- CoGen Redesign

BIM/IPD

- Metrics of Success



Façade Lighting Redesign



The New York Times


- Intro
- Building Background
- Proposal

Facade Redesign


- Floor System Redesign
- Core Redesign
- CoGen Redesign

BIM/IPD


Metrics of Success



Façade Lighting Redesign



400W Floodlight



The New York Times


- Intro
- Building Background
- Proposal

Facade Redesign



- Floor System Redesign
- Core Redesign
- CoGen Redesign

BIM/IPD

Metrics of Success



Façade Lighting Redesign



The New York Times


- Intro
- Building Background
- Proposal

Facade Redesign



- Floor System Redesign
- Core Redesign
- CoGen Redesign

BIM/IPD

Metrics of Success



Façade Lighting Redesign



The New York Times


- Intro
- Building Background
- Proposal

Facade Redesign




- Floor System Redesign
- Core Redesign
- CoGen Redesign

BIM/IPD

Metrics of Success



Façade Lighting Redesign



The New York Times

Intro
Building Background
Proposal

Façade Redesign


Floor System Redesign

Core Redesign

CoGen Redesign

BIM/IPD

Metrics of Success



Floor System Redesign

Goals:

- Increase rentable floor space
- Decrease floor-to-floor height

Redesign Opportunities:


- HVAC (UFAD/VAV to Chilled Beams)
- Structural Floor System (Castellated Beams)

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign

Core Redesign
CoGen Redesign

BIM/IPD
Metrics of Success



Structural Analysis

Initial Study


- Investigate the required depth for interstitial space

Assumptions:

- Loading conditions were the same as in the existing building
- UFAD System would be removed

Result:

- 28" Deep Castellated Beam Required




Existing 30'-0" x 40'-0" Perimeter Bay

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign

Core Redesign
CoGen Redesign

BIM/IPD
Metrics of Success



Structural Analysis



Initial Study


Investigate the required depth for interstitial space

Assumptions:

Loading conditions were the same as in the existing building

UFAD System would be removed







Structural Floor System Redesign

Composite Castellated Beams

Allow for Coordination within Interstitial space




Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign

Core Redesign
CoGen Redesign

BIM/IPD
Metrics of Success



Structural Floor System Redesign


Composite Castellated Beams

Allow for Coordination within Interstitial space


Metal Deck

Long Span Metal Deck

Dovetail Ribbed Composite Metal Deck



Long Span Metal Deck (LS)




Dovetail Ribbed Composite Metal Deck (DT)

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign

Core Redesign
CoGen Redesign


BIM/IPD
Metrics of Success




Structural Floor System Redesign

Configuration 1:

- o Maximize Span
- o Minimize Number of Members



(Shoring Required)




Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign

Core Redesign
CoGen Redesign


BIM/IPD
Metrics of Success




Structural Floor System Redesign

Configuration 2:

- o Minimize Shoring






Structural Floor System Redesign


Floor Vibrations Due to Human Activity:
o 0.5% g Peak Acceleration (AISC Design Guide 11)

Option	Deck	f'c (psi)	Slab t (in)		Slab Weight (psf)	Peak Accel. (% g)
			Overall	Topping		
1	EC450 LWC	4000	7	2.5	39	0.58
2	EC450 NWC	4000	7	2.5	49	0.55
3	0.0358	3000	5.25	3.25	63	0.40
4	0.0474	3000	5.25	3.25	49	0.48
Exist.	3 VL1 22	4000	5.5	2.5	53	0.42



Selected Options for Cost Analysis

Configuration	Option	Deck	Conc	Shoring?
1	3	DT	NWC	Yes
	4	DT	LWC	Yes
2	5	DT	NWC	No
	6	DT	LWC	No



Cost Comparison of Floor Configurations

System	Steel Framing	Concrete Floor	Reshoring	Total
Lightweight Concrete - Config. 1	\$ 7,920,000	\$ 82,160,000	\$ 2,490,000	\$ 92,580,000
Normalweight Concrete - Config. 1	\$ 7,920,000	\$ 61,950,000	\$ 2,490,000	\$ 72,370,000
Lightweight Concrete - Config. 2	\$ 8,540,000	\$ 82,160,000	\$ -	\$ 90,700,000
Normalweight Concrete - Config. 2	\$ 8,540,000	\$ 61,950,000	\$ -	\$ 70,490,000

Floor Configurations Conclusions


Existing Floor Configuration

- o Configuration #2 – 10 ft. typical spans
- o Wide-flange Beams
- o Typical Composite Metal Deck

New Floor Configuration

- o Castellated Beams
- o Configuration #2 – 10 ft. typical spans
- o Dovetail deck






Structural Floor System Redesign

Member Check Cantilever & Overhang

- o Used New Loading Conditions
- o Verified Existing was Adequate or Resized Appropriately

Location	Existing Member	New Load		Existing Capacity		Deflection	Adeq.	New Member	New Capacity	
		M _x (k-ft)	V _y (k)	φM _x (k-ft)	φV _y (k)				φM _x (k-ft)	φV _y (k)
Cant.	W12x19	20.47	10.99	92.6	85.7	ok	OK	W12x19	92.6	85.7
Cant.	W14x22 (int)	229.3	36	277	85.7	ok	OK	W14x22	277	85.7
Cant.	W14x22 (ext)	372.56	36	125	94.8	ok	NG	W14x61	1250	156
Cant.	W21x132	745.1	72	1250	426	ok	OK	W21x132	1250	426
Cant.	W21x50	69.09	18.79	418	237	ok	OK	W21x50	418	237
Edge	W12x19	7.21	77	92.6	85.7	ok	OK	W12x19	92.6	85.7
Edge	W18x130	96.39	25.5	1600	387	ok	OK	W18x130	1690	387
Edge	W24x76	117.2	13.5	750	316	ok	OK	W24x76	750	316
Edge	W18x40	577	57.7	254	169	ok	NG	W30x99*	1170	403

*Selected to illustrate the sizing of castellated members.




The New York Times

- Intro
- Building Background
- Proposal

- Façade Redesign
- Floor System Redesign**
- Core Redesign
- CoGen Redesign

- BIM/IPD
- Metrics of Success



HVAC Redesign

- Multiservice Chilled Beams:
 - o Integrated design



www.Halton.com



www.halton.com



www.halton.com

The New York Times

Intro
Building Background
Proposal

Façade Redesign


Floor System Redesign

Core Redesign

CoGen Redesign

BIM/IPD

Metrics of Success



HVAC Redesign

Multiservice Chilled Beams:

- o Integrated design

Typical Layout:

- o 155 beams per floor




The New York Times

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign

Core Redesign
CoGen Redesign

BIM/IPD
Metrics of Success



HVAC Redesign

Multiservice Chilled Beams:

- o Integrated design


Typical Layout:

- o 155 beams per floor

Savings:

- o Energy (10-16%)

Energy Consumption by Floor




The New York Times

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD
Metrics of Success



HVAC Redesign

Multiservice Chilled Beams:
o Integrated design

Typical Layout:
o 155 beams per floor

Savings:
o Energy (10-16%)
o Cost (\$47,000 / month)

20-Year Lifecycle Cost Savings




The New York Times

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign

Core Redesign
CoGen Redesign

BIM/IPD
Metrics of Success



HVAC Redesign

Multiservice Chilled Beams:

- o Integrated design


Typical Layout:

- o 155 beams per floor

Savings:

- o Energy (10-16%)
- o Cost (\$47,000 / month)
- o Emissions (8-16%)

HVAC Associated Emissions by Floor (CO₂e)




The New York Times

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign

Core Redesign
CoGen Redesign

BIM/IPD
Metrics of Success



Office Lighting Redesign



Integrated 35W T5 Direct Pendant




4' T5HO Direct/Indirect Pendant




4' Recessed Cove

N
W S E




The New York Times

- Intro
- Building Background
- Proposal
- Façade Redesign
- Floor System Redesign**
- Core Redesign
- CoGen Redesign
- BIM/IPD
- Metrics of Success




Office Lighting Redesign




The New York Times

- Intro
- Building Background
- Proposal
- Façade Redesign
- Floor System Redesign**
- Core Redesign
- CoGen Redesign
- BIM/IPD
- Metrics of Success




Office Lighting Redesign




The New York Times

- Intro
- Building Background
- Proposal
- Façade Redesign
- Floor System Redesign**
- Core Redesign
- CoGen Redesign
- BIM/IPD
- Metrics of Success




Office Lighting Redesign





The New York Times

- Intro
- Building Background
- Proposal
- Façade Redesign
- Floor System Redesign**
- Core Redesign
- CoGen Redesign
- BIM/IPD
- Metrics of Success




Office Lighting Redesign



- Intro
- Building Background
- Proposal

- Façade Redesign
- Floor System Redesign**
- Core Redesign
- CoGen Redesign

- BIM/IPD
- Metrics of Success



Cost of Proposed Floor System


- o Cost addition of extra floor

	New Floor System
Structure	\$ 2,988,000.00
Raised Floor	\$ 885,000.00
HVAC Cost	\$ 3,328,000.00
Plumbing Cost	\$ 303,000.00
Electrical Cost	\$ 2,915,000.00
Communications	\$ 1,027,000.00
Interiors	\$ 607,000.00
Furnishing	\$ 215,000.00
	\$ 12,268,000.00

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD
Metrics of Success



Cost of Proposed Floor System

- o Cost addition of extra floor
- o Additional SF of leasable area


Additional Rent Annually	21,000 SF	\$ 60 / SF Year	\$ 1.26 million Year
--------------------------	-----------	--------------------	-------------------------

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign

Core Redesign
CoGen Redesign


BIM/IPD
Metrics of Success



Cost of Proposed Floor System

- o Cost addition of extra floor
- o Additional SF of leasable area
- o Chilled beam cost savings


Yearly Energy Costs by Floor



Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD
Metrics of Success



Cost of Proposed Floor System

- o Cost addition of extra floor
- o Additional SF of leasable area
- o Chilled beam cost savings
- o Overall cost comparison

Additional System Cost	\$ 12,268,000
Additional Rent	\$ 1,260,000
Energy Savings	\$ 565,800
Payback Period	6.72 years

The New York Times

Intro
Building Background
Proposal

Façade Redesign


Floor System Redesign

Core Redesign

CoGen Redesign



BIM/IPD

Metrics of Success



Integrated Design

- o Constructability
- o BIM Use Analysis
 - o 3D Coordination
- o Parties Involved
 - o Structural
 - o Mechanical
 - o Lighting / Electrical
 - o Construction Management
- o Outcome



The New York Times


Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign

Core Redesign

CoGen Redesign

BIM/IPD
Metrics of Success




Core Redesign

Goals:

- o Increase rentable floor space
- o Explore trade issues (Concrete vs. Steel Core)
- o Explore cost for core redesign

Redesign Opportunities:

- o Reconfigure core layout structurally and architecturally
- o Decrease footprint of the structural core
- o Service Spaces




The New York Times

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign
Core Redesign
CoGen Redesign


BIM/IPD
Metrics of Success




Core Configuration

Maintain structural symmetry

- o Reduces torsional effects due to lateral loads
- o Center of geometry converges with center of pressure, center of mass, and center of rigidity




- Intro
- Building Background
- Proposal
- Façade Redesign
- Floor System Redesign
- Core Redesign**
- CoGen Redesign
- BIM/IPD
- Metrics of Success




Core Configuration

Maintain flexibility of space Example: Floors 46 - 50

Existing Configuration



New Configuration




The New York Times


Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign
Core Redesign
CoGen Redesign


BIM/IPD
Metrics of Success




Elevator Configuration



26 Passenger Elev.
2 Service Elev.




Feasibility Study: Elevator Reduction




22 Passenger Elev.
2 Service Elev.

The New York Times

- Intro
- Building Background
- Proposal
- Façade Redesign
- Floor System Redesign
- Core Redesign**
- CoGen Redesign
- BIM/IPD
- Metrics of Success




Core Configuration



26 Passenger Elev.
2 Service Elev.

Existing Configuration




26 Passenger Elev.
2 Service Elev.

Final Configuration


BIM TEAM 3: MATT HEDRICK | KYLE HORST | CASEY LEMAN | ANDRES PEREZ

The New York Times

- Intro
- Building Background
- Proposal
- Façade Redesign
- Floor System Redesign
- Core Redesign**
- CoGen Redesign
- BIM/IPD
- Metrics of Success



Core Configuration



Existing Lobby




New Lobby Rendering

- Intro
- Building Background
- Proposal

- Façade Redesign
- Floor System Redesign
- Core Redesign**
- CoGen Redesign


- BIM/IPD
- Metrics of Success



Service Space Configuration


Area	Existing SF	New SF
Mechanical	360 SF	347 SF
Electrical	180 SF	182 SF
Risers	235 SF	206 SF
Stairs	297 SF	303 SF
Tenant Space	277 SF	267 SF

Service Elevators



The New York Times

- Intro
- Building Background
- Proposal
- Façade Redesign
- Floor System Redesign
- Core Redesign**
- CoGen Redesign
- BIM/IPD
- Metrics of Success



Service Space Configuration

Bus Duct Vs Conduit Analysis

Existing Conditions in NYT Portion

- 18 3 1/2" Conduit Feeders
Powers Lighting and Appliance Panels
- 6 3 1/2" Conduit Feeders
Powers Mechanical Equipment Panels

Proposed Redesign

- 2 2500 Amp Aluminum Bus Duct Feeders
Powers Lighting and Appliance Panels
- 1 1600 Amp Aluminum Bus Duct Feeder
Powers Mechanical Equipment Panels

Bus Duct V

Total Cost

Bus Duct: \$1.5 million

Conduit: \$1.5 million

Space Com

Bus Duct: 100 sq ft
Conduit: 200 sq ft

Benefit of


Possibility of Expansion Without Adding Additional Feeders



- Intro
- Building Background
- Proposal



- Façade Redesign
- Floor System Redesign
- Core Redesign
- CoGen Redesign

- BIM/IPD
- Metrics of Success



Lateral Force Resisting System


Concrete Shear Wall Core w/ Outriggers on the 28th Mechanical Floor



- Intro
- Building Background
- Proposal

- Façade Redesign
- Floor System Redesign
- Core Redesign**
- CoGen Redesign

- BIM/IPD
- Metrics of Success



Lateral Force Resisting System

Initial Design Parameters

Assumed Serviceability Governed Design

SRSS – Period of Vibration

- 10% of 10.8s (Existing Design)

Serviceability Limit States Under Wind Load -


Lawrence G. Griffis (AISC 1993)

Lateral Drift & Deflection

- Wind - $H/450 = 19.88''$ (Existing Design)
D+0.5L+0.7W (ASCE 7-05, CC.1.2)
- Seismic – $0.015h_{sx}$
1.0 E

Design checked for Strength


Existing Period of Vibration	
N/S	6.8 s
E/W	6.2 s
Tors. *	5.6 s
* Assumed	



ETABS Analytical Model

The New York Times

- Intro
- Building Background
- Proposal
- Façade Redesign
- Floor System Redesign
- Core Redesign**
- CoGen Redesign
- BIM/IPD
- Metrics of Success



Lateral Force Resisting System

Concrete Compressive Strength


- 8 ksi
- 10 ksi

Shear Wall Thickness

- 20"
- 24"
- 30"

Coupling Beams


- o 36" Depth
- o Width Dependent upon Support



Intro
 Building Background
 Proposal

Façade Redesign
 Floor System Redesign
Core Redesign
 CoGen Redesign


BIM/IPD
 Metrics of Success




Lateral Force Resisting System

Shear Wall Design: Lobby Level

Level	F_x (ksf)	Wall t, E/W Direction (m)	Wall t, N/S Direction (m)
Base - 30	10	24	30
31-40	8	24	24
41-53	8	20	24




N
 W S E



- Intro
- Building Background
- Proposal

- Façade Redesign
- Floor System Redesign
- Core Redesign**
- CoGen Redesign


- BIM/IPD
- Metrics of Success




Lateral Force Resisting System

Shear Wall Design: Level 2 – Level 28

Level	F_x (ksf)	Wall t, E/W Direction (m)	Wall t, N/S Direction (m)
Base - 30	10	24	30
31-40	5	24	24
41-53	5	20	24




N
W S E



- Intro
- Building Background
- Proposal

- Façade Redesign
- Floor System Redesign
- Core Redesign
- CoGen Redesign


- BIM/IPD
- Metrics of Success




Lateral Force Resisting System

Shear Wall Design: Level 29 – Roof

Level	F _v (ksf)	Wall t, E/W Direction (m)	Wall t, N/S Direction (m)
Base - 30	10	24	30
31-40	5	24	24
41-53	5	20	24




N
W
S
E



- Intro
- Building Background
- Proposal



- Façade Redesign
- Floor System Redesign
- Core Redesign**
- CoGen Redesign

- BIM/IPD
- Metrics of Success




Lateral Force Resisting System

Outrigger Design: 28th Mechanical Floor





- Intro
- Building Background
- Proposal
- Façade Redesign
- Floor System Redesign
- Core Redesign**
- CoGen Redesign
- BIM/IPD
- Metrics of Success




Lateral Force Resisting System

Outrigger Design: 28th Mechanical Floor





- Intro
- Building Background
- Proposal
- Façade Redesign
- Floor System Redesign
- Core Redesign**
- CoGen Redesign
- BIM/IPD
- Metrics of Success



Lateral Force Resisting System


Outrigger Design: 28th Mechanical Floor



Intro
 Building Background
 Proposal

Façade Redesign
 Floor System Redesign
Core Redesign
 CoGen Redesign

BIM/IPD
 Metrics of Success



Lateral Force Resisting System

Serviceability Governed Design – Assumption Confirmed

SRSS – Period of Vibration

o 10% of 10.8s (Existing Design) ✓

Mode	Direction	T(sec.)
1	E/W	7.31
2	N/S	6.57
3	Tor	5.51
SRSS		11.2677
% of Existing		4.417

Lateral Drift & Deflection


- o Wind - $H/450 = 19.88''$ (Existing Design) ✓
- o Seismic – $0.015h_{sx}$ ✓

Direction	Displ. (in)	H/450 (in)	Compliance?
N/S	10.9	19.88	ok
E/W	7.1	19.88	ok

Direction	Level	h_{sx} (ft)	Seismic			Wind		
			$0.015 h_{sx}$	Calculated SD	Compliance ?	h/450	SD from ETABS	Compliance ?
E/W	41	13.26	0.1989	0.0125	ok	0.029467	0.0009	ok
N/S	37	13.26	0.1989	0.009	ok	0.029467	0.001	ok

Strength Check – Members Adequate

- Intro
- Building Background
- Proposal
- Façade Redesign
- Floor System Redesign
- Core Redesign**
- CoGen Redesign
- BIM/IPD
- Metrics of Success



Cost and Schedule Changes


Cost of concrete core vs. existing steel core

- General conditions changes
- o Superstructure schedule
 - o GC cost changes
 - o Constructability

Overall Cost Analysis

Item	Quantity	Cost
Steel Core		\$ (37,171,395)
Concrete Core	21,500 CY	\$ 18,676,730
Crane Addition	2.5 Month	\$ 81,700
Temporary Heating	2 Winters	\$ 4,000,000
Upfront Savings		\$ (14,412,965)
*Additional Rent Annually	5,864 SF	\$ 351,840 per year

- Intro
- Building Background
- Proposal
- Façade Redesign
- Floor System Redesign
- Core Redesign**
- CoGen Redesign
- BIM/IPD
- Metrics of Success




Cost and Schedule Changes

Cost of concrete core vs. existing steel core

- General conditions changes
 - o Superstructure schedule
 - o GC cost changes
 - o Constructability

Overall Cost Analysis


01/01/05



Existing Steel Core

Proposed Concrete Core

- Intro
- Building Background
- Proposal
- Façade Redesign
- Floor System Redesign
- Core Redesign**
- CoGen Redesign
- BIM/IPD
- Metrics of Success



Cost and Schedule Changes


Cost of concrete core vs. existing steel core

- General conditions changes
- o Superstructure schedule
 - o GC cost changes
 - o Constructability

Overall Cost Analysis

Item	Quantity	Cost
Steel Core		\$ (37,171,395)
Concrete Core	21,500 CY	\$ 18,676,730
Crane Addition	2.5 Month	\$ 81,700
Temporary Heating	2 Winters	\$ 4,000,000
Upfront Savings		\$ (14,412,965)
*Additional Rent Annually	5,8464 SF	\$ 351,840 per year

- Intro
- Building Background
- Proposal
- Façade Redesign
- Floor System Redesign
- Core Redesign**
- CoGen Redesign
- BIM/IPD
- Metrics of Success



Cost and Schedule Changes

Cost of concrete core vs. existing steel core

- General conditions changes
- o Superstructure schedule
 - o GC cost changes
 - o Constructability

Overall Cost Analysis


Item	Quantity	Cost
Steel Core		\$ (37,171,395)
Concrete Core	21,500 CY	\$ 18,676,730
Crane Addition	2.5 Month	\$ 81,700
Temporary Heating	2 Winters	\$ 4,000,000
Upfront Savings		\$ (14,412,965)
*Additional Rent Annually	5,8464 SF	\$ 351,840 per year

The New York Times




- Intro
- Building Background
- Proposal


- Façade Redesign
- Floor System Redesign
- Core Redesign**
- CoGen Redesign

- BIM/IPD
- Metrics of Success



Lobby Lighting Redesign

-   9" Recessed Downlight
-   8" Recessed Directional Downlight
-   4' Recessed Cove




The New York Times


- Intro
- Building Background
- Proposal

- Façade Redesign
- Floor System Redesign
- Core Redesign
- CoGen Redesign

- BIM/IPD
- Metrics of Success




Lobby Lighting Redesign





The New York Times

- Intro
- Building Background
- Proposal
- Façade Redesign
- Floor System Redesign
- Core Redesign**
- CoGen Redesign
- BIM/IPD
- Metrics of Success



Lobby Lighting Redesign




The New York Times


- Intro
- Building Background
- Proposal

- Façade Redesign
- Floor System Redesign
- Core Redesign
- CoGen Redesign

- BIM/IPD
- Metrics of Success




Lobby Lighting Redesign




The New York Times

- Intro
- Building Background
- Proposal
- Façade Redesign
- Floor System Redesign
- Core Redesign**
- CoGen Redesign
- BIM/IPD
- Metrics of Success




Lobby Lighting Redesign





The New York Times

- Intro
- Building Background
- Proposal
- Façade Redesign
- Floor System Redesign
- Core Redesign**
- CoGen Redesign
- BIM/IPD
- Metrics of Success



Lobby Lighting Redesign




The New York Times

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD
Metrics of Success



Existing System / Goals

Existing System:

- o 1.4 MW Internal Combustion
- o 40% power capacity for NYT
- o 250 ton absorption chiller

Redesign Goals:

- o 100% power capacity for NYT
- o Increased energy cost savings
- o Decreased energy associated emissions
- o All met!




The New York Times

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD
Metrics of Success




Redesign Considerations

Utility Data / Spark Gap

Utility	Yearly \$/Unit	Reference
Natural Gas	\$1.392/Ccf	New York State Public Service Commission
Electric	\$0.249/kWh	New York State Public Service Commission
Steam	\$18.36/Mlb	Consolidated Edison
Water	\$2.31/per(748gals)	New York City Water Board

Spark Gap	
Fuel	Cost / (MMbtu)
Natural Gas	\$ 11.27
Electricity	\$ 72.97
Steam	\$ 15.40
Gap	\$ 61.70


Space Constraints (3000 ft² total)



Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign
Core Redesign
CoGen Redesign



BIM/IPD
Metrics of Success



Redesign Consideration

Redesign Considerations:


- o Building thermal and electrical loads



Intro
 Building Background
 Proposal

Façade Redesign
 Floor System Redesign
 Core Redesign
CoGen Redesign

BIM/IPD
 Metrics of Success



Redesign Alternatives

Prime Movers

CHP System	Existing	Alternative 1	Alternative 2	Alternative 3
Prime Movers				
Reciprocating Engine(s)	2 - /00 kW	6 - /00 kW	2 - 700 kW 1 - 1300kW	2 - /00 kW
Gas Turbine(s)	-	-	-	1 - 1300kW
Make, Model	Caterpillar, G3516 LE	Caterpillar, G3516 LE	Caterpillar, G3516 LE Caterpillar, DM5496	Caterpillar, G3516 LE Solar, Saturn 70
Fuel	Natural Gas	Natural Gas	Natural Gas	Natural Gas
Total Floor Area (ft ²)	1,600	4,800	2,970	2,735
Total Weight (lbs)	50,310	106,520	65,720	50,310

Gas Turbines




IC Engines



Intro
 Building Background
 Proposal

Façade Redesign
 Floor System Redesign
 Core Redesign
CoGen Redesign

BIM/IPD
 Metrics of Success



Redesign Alternatives

Prime Movers

CHP System	Existing	Alternative 1	Alternative 2	Alternative 3
Prime Movers				
Reciprocating Engine(s)	2 - 700 kW	6 - 700 kW	2 - 700 kW 1 - 1300 kW	2 - 700 kW
Gas Turbine(s)	-	-	-	1 - 1300 kW
Make, Model	Caterpillar, G3516 LE	Caterpillar, G3516 LE	Caterpillar, G3516 LE Caterpillar, DM5496	Caterpillar, G3516 LE Solar, Saturn 70
Fuel	Natural Gas	Natural Gas	Natural Gas	Natural Gas
Total Floor Area (ft ²)	1,600	4,800	2,970	2,735
Total Weight (lbs)	35,340	106,520	65,720	50,590

Existing System: 1,400 kW




IC Engines

Intro
 Building Background
 Proposal

Façade Redesign
 Floor System Redesign
 Core Redesign
CoGen Redesign

BIM/IPD
 Metrics of Success



Redesign Alternatives

Prime Movers

CHP System	Existing	Alternative 1	Alternative 2	Alternative 3
Prime Movers				
Reciprocating Engine(s)	2 - 700 kW	6 - 700 kW	2 - 700 kW 1 - 1300kW	2 - 700 kW
Gas Turbine(s)	-	-	-	1 - 1300kW
Make, Model	Caterpillar, G3516 LE	Caterpillar, G3516 LE	Caterpillar, G3516 LE Caterpillar, DM5496	Caterpillar, G3516 LE Solar, Saturn 70
Fuel	Natural Gas	Natural Gas	Natural Gas	Natural Gas
Total Floor Area (ft ²)	1,600	4,800	2,970	2,735
Total Weight (lbs)	50,310	106,020	65,720	50,310

Alternative 1: 4,200 kW




IC Engines

Intro
 Building Background
 Proposal

Façade Redesign
 Floor System Redesign
 Core Redesign
CoGen Redesign

BIM/IPD
 Metrics of Success



Redesign Alternatives

Prime Movers

CHP System	Existing	Alternative 1	Alternative 2	Alternative 3
Prime Movers				
Reciprocating Engine(s)	2 - 700 kW	6 - 700 kW	2 - 700 kW 1 - 1300kW	2 - 700 kW
Gas Turbine(s)	-	-	-	1 - 1300kW
Make, Model	Caterpillar, G3516 LE	Caterpillar, G3516 LE	Caterpillar, G3516 LE Caterpillar, DM5496	Caterpillar, G3516 LE Solar, Saturn 70
Fuel	Natural Gas	Natural Gas	Natural Gas	Natural Gas
Total Floor Area (ft ²)	1,600	4,800	2,970	2,735
Total Weight (lbs)	50,310	106,020	63,720	50,310

Alternative 2: 2,700 kW



+




IC Engines

1,300 kW IC Engine

Intro
 Building Background
 Proposal

Façade Redesign
 Floor System Redesign
 Core Redesign
CoGen Redesign

BIM/IPD
 Metrics of Success



Redesign Alternatives

Prime Movers

CHP System	Existing	Alternative 1	Alternative 2	Alternative 3
Prime Movers				
Reciprocating Engine(s)	2 - 700 kW	6 - 700 kW	2 - 700 kW 1 - 1300kW	2 - 700 kW
Gas Turbine(s)	-	-	-	1 - 1300kW
Make, Model	Caterpillar, G3516 LE	Caterpillar, G3516 LE	Caterpillar, G3516 LE Caterpillar, DM5496	Caterpillar, G3516 LE Solar, Saturn 20
Fuel	Natural Gas	Natural Gas	Natural Gas	Natural Gas
Total Floor Area (ft ²)	1,600	4,800	2,970	2,735
Total Weight (lbs)	50,310	106,520	65,720	50,340

Alternative 3: 2,700 kW



+




IC Engines

1,300 kW Gas Turbine

Intro
Building Background
Proposal


Façade Redesign
Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD
Metrics of Success




Redesign Alternatives

IC Engine: Cooling Load Potential




Gas Turbine: Excess Thermal



Intro
 Building Background
 Proposal

Façade Redesign
 Floor System Redesign
 Core Redesign
CoGen Redesign


BIM/IPD
 Metrics of Success




Redesign Alternatives

Energy / Emissions

CHP System	Existing	Alternative 1	Alternative 2	Alternative 3
Energy / Emissions				
Max Power Output (kW)	1,400	4,200	2,700	2,700
Yearly Power Output (kWh)	12,101,254	22,731,012	18,388,809	7,030,255
Max Thermal Rejection (Mbh)	9,340	28,020	15,240	18,940
Usable Heat Rejection (Mbh/year)	66,509,219	80,267,534	73,141,027	81,940,305
Fuel Consumption (scf/kWh)	12.49	12.49	12.11	13.35
Max Fuel Consumption (scf/hr)	17,485	52,455	32,692	36,045
Emissions Reduction (lbs CO ₂ e/year)	16,215,680	30,459,556	24,641,004	10,442,812






Redesign Alternatives

Energy Costs

CHP System	Existing	Alternative 1	Alternative 2	Alternative 3
Costs				
Installed Costs (\$)	\$5,600,000	\$16,800,000	\$10,800,000	\$12,100,000
Maintenance Costs (\$/kWh)	\$0.005	\$0.005	\$0.005	\$0.005
Maintenance Costs (\$/year)	\$60,506	\$113,655	\$91,944	\$205,530
Building Energy Costs (\$/year)	\$11,310,248	\$9,766,130	\$10,443,122	\$10,649,749
Total Energy Cost Savings (\$/year)	\$2,272,786	\$3,816,905	\$3,139,912	\$2,933,285
Payback Period (years)	0.00	7.83	6.71	14.29


Total Energy Costs: \$13.5 million for SHP



Intro
 Building Background
 Proposal

Façade Redesign
 Floor System Redesign
 Core Redesign
CoGen Redesign


BIM/IPD
 Metrics of Success



Redesign Alternatives

Simple Payback Period


CHP System	Existing	Alternative 1	Alternative 2	Alternative 3
Costs				
Installed Costs (\$)	\$5,600,000	\$16,800,000	\$10,800,000	\$12,100,000
Maintenance Costs (\$/kWh)	\$0.005	\$0.005	\$0.005	\$0.005
Maintenance Costs (\$/year)	\$60,506	\$113,655	\$91,944	\$205,530
Building Energy Costs (\$/year)	\$11,310,248	\$9,766,130	\$10,443,122	\$10,649,749
Total Energy Cost Savings (\$/year)	\$2,272,786	\$3,816,905	\$3,139,912	\$2,933,285
Payback Period (years)	0.00	7.83	6.71	14.29



Intro
 Building Background
 Proposal

Façade Redesign
 Floor System Redesign
 Core Redesign
CoGen Redesign

BIM/IPD
 Metrics of Success



Redesign Alternatives

Summary

Overall Comparison	Existing	Alternative 1	Alternative 2	Alternative 3
Energy Cost	✗	😊	😊	😊
Source Energy Emissions	✗	😊	😊	😊
Payback Period	😊	😊	😊	✗
System Footprint	😊	✗	😊	😊

Alternative 2: 2,700 kW



+




IC Engines

1,300 kW IC Engine

Intro
 Building Background
 Proposal

Façade Redesign
 Floor System Redesign
 Core Redesign
CoGen Redesign

BIM/IPD
 Metrics of Success




Redesign Alternatives

Summary

Overall Comparison	Existing	Alternative 1	Alternative 2	Alternative 3
Energy Cost	✘	😊	😊	😊
Source Energy Emissions	✘	😊	😊	😊
Payback Period	😊	😊	😊	✘
System Footprint	😊	✘	😊	😊

Alternative 2: \$10 million in savings over 20 years




The New York Times

- Intro
- Building Background
- Proposal

- Façade Redesign
- Floor System Redesign
- Core Redesign
- CoGen Redesign

BIM/IPD
Metrics of Success



Integrated Project Delivery Process




The New York Times

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD

Metrics of Success



BIM Goals

Building Information Modeling Process:

BIM Goals

Group Goals:

- Enhance communication and information flow
- Visualize project changes

BIM Use Analysis

Workflows




The New York Times

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD
Metrics of Success



BIM Goals

Building Information Modeling Process:

BIM Goals

Group Goals:

- o Enhance communication and information flow
- o Visualize project changes

BIM Use Analysis

Workflows




The New York Times

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD
Metrics of Success



BIM Use Analysis

Building Information Modeling Process:

BIM Goals

Group Goals:

- Enhance communication and information flow
- Visualize project changes

BIM Use Analysis

Workflows

BIM Uses Analysis

Design Authoring

Design Review

3D Coordination


Phase Planning

The New York Times

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD
Metrics of Success



BIM Workflows

Building Information Modeling Process:


BIM Goals

Group Goals:

- o Enhance communication and information flow
- o Visualize project changes

BIM Use Analysis

Workflows



The New York Times

- Intro
- Building Background
- Proposal

- Façade Redesign
- Floor System Redesign
- Core Redesign
- CoGen Redesign

BIM/IPD

Metrics of Success

Metrics of Success




Increased Profitability

- Operating Costs
- Leasable Space

Increased Marketability

- Sustainability
- Iconic Image

Yearly Energy Cost Savings by Category




The New York Times

- Intro
- Building Background
- Proposal

- Façade Redesign
- Floor System Redesign
- Core Redesign
- CoGen Redesign

- BIM/IPD
- Metrics of Success**



Metrics of Success



www.international-pc.com/


Increased Profitability

- Operating Costs
- Leasable Space

Increased Marketability

- Sustainability
- Iconic Image

Additional Square Footage	26,864 SF
Additional Rent	\$ 1,601,840



The New York Times

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD

Metrics of Success

Metrics of Success



www.international-pc.com/


Increased Profitability

- Operating Costs
- Leasable Space

Increased Marketability

- Sustainability
- Iconic Image

Building Energy Use Associated Emissions (CO₂e)



35% Energy Reduction


The New York Times

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD

Metrics of Success



Metrics of Success



www.international-pc.com/

Increased Profitability

- Operating Costs
- Leasable Space

Increased Marketability

- Sustainability
- Iconic Image



The New York Times

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD

Metrics of Success

Metrics of Success




www.international-pc.com/

Increased Profitability

- Operating Costs
- Leasable Space

Increased Marketability

- Sustainability
- Iconic Image



The New York Times

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD

Metrics of Success

Metrics of Success

Increased Profitability



- Operating Costs
- Leasable Space

Increased Marketability

- Sustainability
- Iconic Image



www.international-pc.com/




The New York Times

Intro
Building Background
Proposal

Façade Redesign
Floor System Redesign
Core Redesign
CoGen Redesign

BIM/IPD

Metrics of Success



Metrics of Success



www.international-pc.com/

Increased Profitability

- Operating Costs
- Leasable Space

Increased Marketability

- Sustainability
- Iconic Image

Façade	
Upfront Cost	\$ 18.7 million
Annual Energy Savings	\$ 800,000
Payback Period	23.4 years

Floor System	
Upfront Cost	\$ 12.3 million
Annual Energy Savings	\$ 565,800
Annual Added Rent	\$ 1.24 million
Payback Period	6.72 years


Core	
Upfront Cost	(\$ 14.4 million)
Annual Added Rent	\$ 351,840
Payback Period	NA

The New York Times

- Intro
- Building Background
- Proposal

- Façade Redesign
- Floor System Redesign
- Core Redesign
- CoGen Redesign

- BIM/IPD
- Metrics of Success**



Metrics of Success



www.international-pc.com/

Increased Profitability

- Operating Costs
- Leasable Space

Increased Marketability

- Sustainability
- Iconic Image

Overall Building	
Upfront Cost	\$ 17 million
Annual Added Rent	\$ 1.6 million
Annual Energy Savings	\$ 2.2 million
Payback Period	4.5 years


The New York Times

- Intro
- Building Background
- Proposal

- Façade Redesign
- Floor System Redesign
- Core Redesign
- CoGen Redesign

BIM/IPD




Metrics of Success



Lessons Learned



www.international-pc.com/





Acknowledgements

Thank you to the following for all the support, assistance and guidance:

Architectural Engineering Faculty and Staff

- IPD/BIM Thesis Advisors:
Kevin Parfitt
Bob Holland
- Mechanical Thesis Advisor:
Jelena Srebric, Ph.D.
- Structural Thesis Advisor:
Andres Lepage, Ph. D
- Lighting/Electrical Thesis Advisors:
Kevin Houser, Ph. D
Theodore Dannerth
- Construction Management Thesis Advisors:
Chimay Anumba, Ph. D
Jim Faust
- CHP Instruction:
James Freihaut, Ph.D.

Sponsors and Consultants

- Project Sponsors:
Leonhard Center
Thornton Tomasetti
- Project Participants:
The New York Times Company
WSP Flack + Kurtz
Turner Construction
- CHP Contacts:
Dave Yanni | Director, Business Development and Operations,
Endurant Energy, LLC
Randy Musselman | Engineering, Cleveland Brothers,
Power Systems Division
- High-rise Consultant:
Bob McNamara

Fellow BIM Teams for their support in this collaborative process

THANK YOU to All of our friends and family for their love and support!



Questions/Comments