Park Potomac Office Building "E"



Kyle Wagner I Structural Option
AE Senior Thesis I Spring 2010
Faculty Consultant I Prof. Kevin Parfitt

- •Project Information
- •Existing Structural System
- •Problem Statement and Solution
- •Structural Depth Study
- •Cost and Schedule Analysis
- •Additional Topics
- •Conclusions
- •Acknowledgements
- •Questions and Comments

Project Information

- •Existing Structural System
- •Problem Statement and Solution
- •Structural Depth Study
- •Cost and Schedule Analysis
- •Additional Topics
- Conclusions
- Acknowledgements
- Questions and Comments

Project Information

- •Located off I-270 in Potomac, MD
- •Part of Park Potomac Place
- •Townhomes, Office Space, Retail, Dining
- •Prominent location within Community
 - •Focal point from Cadbury Ave.
 - •Face of community from I-270



View from Cadbury Ave



www.parkpotomacplace.com

Project Information

- •Existing Structural System
- •Problem Statement and Solution
- •Structural Depth Study
- •Cost and Schedule Analysis
- •Additional Topics
- •Conclusions
- Acknowledgements
- Questions and Comments

Project Information

- •Two levels mostly underground parking
 - •100,000+ SF each
- •Seven levels of mostly office space
 - •Approx. 25,000 SF each



Building Footprint




North Entrance to Parking Levels

- Project Information
- •Existing Structural System
- •Problem Statement and Solution
- •Structural Depth Study
- •Cost and Schedule Analysis
- •Additional Topics
- Conclusions
- Acknowledgements
- Questions and Comments

Existing Structural System

- •Underground Parking all Cast-in-place concrete
- •7" Thick slab post-tensioned in N-S direction
- •72" x 20" D Beams post-tensioned in E-W direction
- •Concrete Moment Frames in both directions
- •Long Spans accomplished
 - •Flexibility for Tenant
- •12' Cantilever at N, S ends






Existing Structural System

- Project Information
- •Existing Structural System
- Problem Statement and Solution
- •Structural Depth Study
- •Cost and Schedule Analysis
- •Additional Topics
- Conclusions
- Acknowledgements
- •Questions and Comments

Problem Statement

- Concrete structure results in large building self weight
 - Larger gravity members result
 - Large mat foundations at soil level
 - Central Foundation 52' x 64' x 60" Deep
- Longer schedule duration from concrete construction
- End Result: Negative Cost and Schedule Implications



Existing Foundation Plan

- Project Information
- •Existing Structural System
- Problem Statement and Solution
- •Structural Depth Study
- •Cost and Schedule Analysis
- Additional Topics
- Conclusions
- Acknowledgements
- Questions and Comments

Problem Solution

- Reduce building self weight by utilizing a steel structure
- Composite Beams and lightweight concrete used
- To maintain integrity of existing design:
 - Maintain current column layout
 - Maintain current ceiling heights in Tenant Spaces
 - Maintain current MEP Spaces
- Braced Frames used to resist lateral forces
- Steel construction likely to reduce construction schedule
- Parking levels will remain unchanged

- Project Information
- •Existing Structural System
- Problem Statement and Solution
- •Structural Depth Study
- •Cost and Schedule Analysis
- •Additional Topics
- Conclusions
- Acknowledgements
- •Questions and Comments

Project Goals

- Reduce building self weight
- Maintain integrity of tenant spaces
- Reduce overall cost
- Reduce schedule duration

- Project Information
- •Existing Structural System
- •Problem Statement and Solution
- Structural Depth Study
- •Cost and Schedule Analysis
- •Additional Topics
- •Conclusions
- Acknowledgements
- •Questions and Comments

Design Loads

- Design Loads
 - •ASCE 7-05
- Superimposed Dead Loads
 - •5 psf Floor
 - •10 psf Roof
- •Flat Roof Snow Load
 - •21 psf

| Floor Live Loads | | | | | |
|-----------------------------|----------------------------|------------------------|--|--|--|
| Area | Design Load (psf) | ASCE 7-05 Load (psf) | | | |
| Assembly Areas | 100 | 100 | | | |
| Corridors | 100 | 100 | | | |
| Corridors Above First Floor | 80 | 80 | | | |
| Lobbies | 100 | 100 | | | |
| Marquees & Canopies | 75 | 75 | | | |
| Mechanical Rooms | 150 | 125 | | | |
| Offices | 80 + 20 psf Partitions | 50 + 20 psf Partitions | | | |
| Parking Garages | 50 | 40 | | | |
| Plaza, Top Floor Parking | Fire Truck Load or 250 psf | 250 | | | |
| Retail- First Floor | 100 | 100 | | | |
| Stairs and Exitways | 100 | 100 | | | |
| Storage (Light) | 125 125 | | | | |


Live Load Values

- Project Information
- •Existing Structural System
- Problem Statement and Solution
- •Structural Depth Study
- •Cost and Schedule Analysis
- •Additional Topics
- Conclusions
- Acknowledgements
- Questions and Comments


Gravity System Design

- •5 ½" Thick Slab on 2", 18 Gage Metal Decking
 - •Provides adequate 2 hour fire rating between floors
- •Beams spacing does not exceed 10'
 - Unshored
 - •Minimize number
 - of beams required
- •Columns spliced every

other floor



RAM Model



Typical Floor Layout

- Project Information
- •Existing Structural System
- Problem Statement and Solution
- •Structural Depth Study
- •Cost and Schedule Analysis
- •Additional Topics
- Conclusions
- Acknowledgements
- Questions and Comments

Cantilevered Ends

- 12' Cantilever on North and South Ends
- Unobstructed glass around building corners



- •Four beams used to transfer load back to columns
- •Beam required:
 - •W18x55



•Moment connection at interior to balance moment at column

- •Moment from cantilever: 575 ft-k
- •Moment from interior: 376 ft-k
- •Moment to column: 199 ft-k
- •Design for moment and axial due to
- gravity load
- •Final Design shown at right

William Willia

- Project Information
- •Existing Structural System
- Problem Statement and Solution
- •Structural Depth Study
- •Cost and Schedule Analysis
- •Additional Topics
- Conclusions
- Acknowledgements
- •Questions and Comments

Floor Depth Comparison

- Existing post-tensioned system
 - 20" depth at beams



- 51/4
 - - Deepest Beam: W27x84
 - Floor Depth Approx. 32"

• Maintain ceiling heights and MEP Spaces



- Increase overall building height
 - No code restrictions
 - Increase by 12" per floor
 - Overall height increase by 7'
 - Recalculate lateral loads

- Project Information
- •Existing Structural System
- Problem Statement and Solution
- Structural Depth Study
- •Cost and Schedule Analysis
- •Additional Topics
- Conclusions
- Acknowledgements
- •Questions and Comments


Lateral Loads

- Wind: Method 2 of ASCE 7-05 Chapter 6
 - Assume wind negligible beneath plaza level
- Seismic: ELFP of ASCE 7-05 Chapter 11
 - Seismic Design Category B
 - Seismic Base Level taken at plaza level
- Wind controlled for strength and serviceability

- Project Information
- •Existing Structural System
- Problem Statement and Solution
- •Structural Depth Study
- •Cost and Schedule Analysis
- •Additional Topics
- Conclusions
- Acknowledgements
- Questions and Comments

ETABS Model

- 7 Load combinations, 4 wind cases, accidental torsion (5% ecc.) due to seismic all manually included
- Floors modeled as rigid diaphragms
 - Loads distributed based on relative stiffnesses of frames
- Only lateral system modeled
- Gravity loads applied using additional area mass to diaphragm




ETABS Model


- Project Information
- •Existing Structural System
- Problem Statement and Solution
- Structural Depth Study
- •Cost and Schedule Analysis
- •Additional Topics
- Conclusions
- Acknowledgements
- Questions and Comments


Braced Frame Design

- Symmetry in Geometry and Stiffness
- Loads distributed evenly to each frame



- SAP used to calculate forces in braces for critical load combination
- •Critical load combination used to design columns
- •Final Brace Frame Design shown at right
- •E-W Frames larger than N-S Frames







- Project Information
- •Existing Structural System
- Problem Statement and Solution
- •Structural Depth Study
- •Cost and Schedule Analysis
- •Additional Topics
- Conclusions
- Acknowledgements
- •Questions and Comments

Lateral Analysis

- Primary controlling load case was 0.9D+1.6W
- Controlling wind case was Wind Case 1
- Center of mass and rigidity both at geometric center
- Overall building torsion was negliglible
- Wind drift within L/400
- Seismic drift found to be well within limitations

- Project Information
- •Existing Structural System
- Problem Statement and Solution
- Structural Depth Study
- •Cost and Schedule Analysis
- •Additional Topics
- •Conclusions
- Acknowledgements
- •Questions and Comments





- Steel Structure Foundations
 - •17' x 17' x 34" Deep (U.N.O.)

- Project Information
- •Existing Structural System
- Problem Statement and Solution
- •Structural Depth Study
- •Cost and Schedule Analysis
- •Additional Topics
- Conclusions
- Acknowledgements
- •Questions and Comments


Cost/ Schedule

- Detailed takeoffs completed for both systems
- Foundations cost reduced 78%
- Total Structure cost reduced by 25%
- \bullet Schedule predicted to be decreased by approx. 10 months
 - •General conditions savings not factored into cost results

| Original Structure | | | | | | |
|------------------------------|-------------|-------------|-----------|-------------|---------|--|
| | Mat'l | Labor | Equipment | Total | COST/SF | |
| Foundations | \$272,327 | \$59,403 | \$250 | \$331,980 | \$1.90 | |
| Superstructure | \$2,532,939 | \$1,594,087 | \$48,370 | \$4,175,396 | \$23.86 | |
| | | | | | | |
| Total Incl. Additional Costs | | | | \$27.83 | | |
| Steel Redesign | | | | | | |
| | Mat'l | Labor | Equipment | Total | COST/SF | |
| Foundations | \$54,082 | \$17,076 | \$1,874 | \$73,033 | \$0.42 | |
| Superstructure | \$2,669,627 | \$290,079 | \$114,563 | \$3,074,269 | \$17.57 | |
| | | | | | | |
| | | | | | | |
| Total Incl. Additio | nal Costs | | | | \$19.43 | |
| | | | | | | |

- •Assuming \$50 per SF of building enclosure
 - •\$224,000 additional
 - •Final Steel cost of \$20.69 per SF


- •Project Information
- •Existing Structural System
- •Problem Statement and Solution
- •Structural Depth Study
- •Cost and Schedule Analysis
- •Additional Topics
- •Conclusions
- Acknowledgements
- •Questions and Comments



- Project Information
- •Existing Structural System
- Problem Statement and Solution
- •Structural Depth Study
- •Cost and Schedule Analysis
- Additional Topics
- •Conclusions
- Acknowledgements
- Questions and Comments


Further Improvements

- Potential to reduce floor depth
 - From Earlier:
 - Deepest Beam: W27x84



- Use W21 x 93 instead
- Constrain 10 beams on each floor
- Floor depth required: 32" → 26"
- Overall height increase by 3.5', not 7'

- Potential to balance additional moment
 - •Unbalanced moment: 199 ft-k



- Decreasing cantilever distance or increase moment on interior
- •Much smaller columns will result

- Project Information
- •Existing Structural System
- •Problem Statement and Solution
- •Structural Depth Study
- •Cost and Schedule Analysis
- •Additional Topics
- •Conclusions
- Acknowledgements
- •Questions and Comments

Conclusions

- Reduce building self weight
- <u>×</u>
- Maintain integrity of tenant spaces



- Reduce overall cost
- Reduce schedule duration



• Steel could have been a viable and beneficial alternative.



Office Building "E"

- Project Information
- •Existing Structural System
- Problem Statement and Solution
- •Structural Depth Study
- •Cost and Schedule Analysis
- •Additional Topics
- Conclusions
- Acknowledgements
- Questions and Comments



- •Project Information
- •Existing Structural System
- •Problem Statement and Solution
- •Structural Depth Study
- •Cost and Schedule Analysis
- •Additional Topics
- •Conclusions
- Acknowledgements
- **•Questions and Comments**

