

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions

Samuel Avila Structural Option April 11, 2006

Advisor: Dr. Thomas Boothby



Samuel Avila Structural Option



Presentation Outline

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions

Building Introduction Problem/Proposal Post-Tensioned One Way Slab Shear Wall Analysis Mechanical Analysis Acoustical Analysis Conclusions



Building Introduction

Introduction

Existing System

Problem

Proposal


Structural System Redesign

Breath work

Conclusions

Location Central Florida Blvd Southwest of UCF's main campus.

Function Student Housing





Building Introduction

Nike Community

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions

7 separate buildings24'0" x 28'0" units40-60 apartment unitsper building

<u>Size</u>

Varies: Footprints range from 14,000 sq ft. to 22,000 sq ft.

4 stories above grade


<u>Cost</u>

\$63 million

Time Frame

Began: August 1999 Completed: July 2002

Samuel Avila Structural Option





Building Introduction

Nike Community

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions

7 separate buildings 24'0" x 28'0" units 40-60 apartment units per building

<u>Size</u>

Varies: Footprints range from 14,000 sq ft. to 22,000 sq ft.

4 stories above grade

<u>Cost</u>

\$63 million

Time Frame

Began: August 1999 Completed: July 2002

Samuel Avila Structural Option



Building that I chose to analyze



Building Introduction

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions

Primary Project Team		
Owner	University of Central Florida	
Architect Hanbury Evans Wright V		
Structural Engineer	TLC Engineering	
Geotechnical Engineer	Nodarse & Associates	
Mechanical Engineer	TLC Engineering	
Contractor	Centex Homes	
Civil Engineer	Vanasse Hangen Brustlin, Inc.	



Building Introduction

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions


Design Codes
American Institute of Steel Construction (AISC)
Load and Resistance Factor Design (LRFD)
American Society for Testing and Materials (ASTM)
Specifications for Structural Concrete (ACI 301)
Specifications for Masonry Structures (ACI 530.1)
American With Disabilities Act (ADA)
Florida Accessibility Code

Design Live Loads			
Roof	20 psf		
Corridors	80 psf		
Mechanical Rooms	150 psf		
Stairs, Public Areas, Lobby	100 psf		
All Other Rooms	40 psf		
Superimposed Dead Loads			
M/E/P	10 psf		
Partitions	20 psf		



Building Introduction

Building Footprint



Samuel Avila Structural Option



Building Introduction

Gravity System

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work


Conclusions

Infinity System

Epicore Metal Deck 4 ¹⁄₂" Concrete Slab Welded Wire Reinforcement

Typical Span

Between 8" Masonry Bearing Walls 12'0" Span in East-West Direction








Building Introduction

Lateral System



Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions

Samuel Avila Structural Option



Building Introduction

Lateral System

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions

		Shear Wall Force Schedule (kips)							
ו		Shear 1		Shear 2		Shear 3		Shear 4	
		Each Floor	Total	Each Floor	Total	Each Floor	Total	Each Floor	Total
	4th Floor	7.21	7.21	6.01	6.01	2.56	2.56	1.07	1.07
	3rd Floor	13.52	20.73	11.27	17.28	4.79	7.35	1.97	3.04
	2nd Floor	13.48	34.21	11.23	28.51	4.77	12.12	1.98	5.02
		Shear 5		Shear 6		Shear 7		Shear 8	
		Each Floor	Total	Each Floor	Total	Each Floor	Total	Each Floor	Total
	4th Floor	2.1	2.1	6.04	6.04	5.18	5.18	1.07	1.07
	3rd Floor	3.94	6.04	11.32	17.36	9.7	14.88	1.97	3.04
	2nd Floor	3.93	9.97	11.28	28.64	9.67	24.55	1.98	5.02

Samuel Avila Structural Option



Building Introduction

Lateral System

Introduction

Existing System

Problem

Proposal

Structural System Redesign


Breath work

Conclusions

Description

Interior and Exterior Masonry Shear Walls

All Walls 8" Masonry Blocks w/ Type S mortar and #5 @ 24" Reinforcement





Problem/Proposal

Introduction **Problem**

Existing System

Problem


Proposal

Structural System Redesign

Breath work

Conclusions

Criteria à Layout Flexibility Existing Floor System Limits the Span Length to 12'0"





Problem/Proposal

Introduction

Existing System

Problem

Proposal


Structural System Redesign

Breath work

Conclusions

Problem Criteria à Layout Flexibility Existing Floor System Limits the Span Length to 12'0"

Bearing Wall Included at Midspan Due to Existing Gravity System



Samuel Avila Structural Option



Problem/Proposal

Structure System Investigation

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions

Analyze Gravity System as a Post-Tensioned One-Way Slab System

Redesign Shear Walls For Additional Loads Due to New Floor System

Mechanical Breadth Study

Investigation to Determine if an Energy Recovery Ventilator (ERV) System is a Feasible Opportunity to Reduce HVAC Operational Costs

Acoustical Breadth Study

Investigation to Verify That the New Structure Meets IBC 2000 Requirements

Acoustics Check For Rooms Adjacent to Air Handling Units





Problem/Proposal

Design Goals (Structural)

Make Units More Flexible By Removing Interior Bearing Wall at Midspan in Each Unit

Minimize Slab Depth So That the Floor to Floor Height Remains Constant

Design Goals (Mechanical/Acoustics)

Maintain or Improve the Quality of Life for All Residents

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions



Post-Tensioned One-Way Slab

Four Case Investigations (ACI 318-02 18.3.3)

Introduction

Existing System

Problem


Proposal

Structural System Redesign

Breath work

Conclusions

- 1. One-Way Simple Span Class U (uncracked)
- 2. One-Way Simple Span Class T (transition)
- 3. One-Way Continuous Span Class U (uncracked)
- 4. One-Way Continuous Span Class T (transition)



Samuel Avila Structural Option



Post-Tensioned One-Way Slab

Flexure/Deflection

Introduction

Existing System

Problem


Proposal


Structural System Redesign

Breath work

Conclusions







AE 2006 Advisor: Dr. Thomas Boothby



Post-Tensioned One-Way Slab

Flexure/Deflection

Introduction

Existing System


Problem

Proposal

Structural System Redesign

Breath work

Conclusions





Post-Tensioned One-Way Slab

Flexure/Deflection

Introduction

Existing System


Problem

Proposal

Structural System Redesign

Breath work

Conclusions





Post-Tensioned One-Way Slab

Tendon Profile Parameters

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions

Distance	Eccentr	icities (in)	Tendon
(ft)	Min	Max	Profile
0	-1.59	0.96	0.50
4	-0.05	1.47	0.73
8	0.85	1.78	0.97
12	1.11	1.88	1.20
16	0.74	1.78	0.97
20	-0.26	1.47	0.73
24	-1.59	0.96	0.50
28	-0.05	1.47	0.73
32	0.85	1.78	0.97
36	1.11	1.88	1.20
40	0.74	1.78	0.97
44	-0.26	1.47	0.73
48	-1.59	0.96	0.50
52	-0.05	1.47	0.73
56	0.85	1.78	0.97
60	1.11	1.88	1.20
64	0.74	1.78	0.97
68	-0.26	1.47	0.73
72	-1.59	0.96	0.50
76	-0.05	1.47	0.73
80	0.85	1.78	0.97
84	1.11	1.88	1.20
88	0.74	1.78	0.97
92	-0.26	1.47	0.73
96	-1.59	0.96	0.50



University of Central Florida's Academic Villages Orlando, Florida **Post-Tensioned One-Way Slab**

Introduction

Existing System


Problem

Proposal

Structural System Redesign

Breath work

Conclusions





Post-Tensioned One-Way Slab

Flexure/Deflection Results

Case InvestigationSlab ThicknessForce Required / ftSimple Span Class U7.5"46.5 K/ftSimple Span Class T7"56.5 K/ftContinuous Span Class U6"68.3 K/ftContinuous Span Class T5"70.7 K/ft

<u>Reinforcment</u>

(2) ¹/₂"Ø 7-wire low-lax steel strands ASTM Grade 270 were used every foot for Regions I & III

(1) ¹/₂"Ø 7-wire low-lax steel strands ASTM Grade 270 was used every foot for Regions II

Introduction

Existing System

Problem

Proposal

Structural System Redesign


Breath work

Conclusions

Samuel Avila Structural Option



Post-Tensioned One-Way Slab



Distance from support (ft)	Wire designation	Area of shear reinforcement (in ²)	Spacing of vertical wire (in)
3	W2.9	0.058	6
8	W2.9	0.058	12
12	W2.9	0.058	24
18	W2.9	0.058	24

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work


Conclusions

Samuel Avila Structural Option



Post-Tensioned One-Way Slab

Shear Results





Post-Tensioned One-Way Slab

Shear Walls

Lateral Forces (kips) Wall 7 Wall 1 Wall 4 **Shear Force Shear Force** Total **Shear Force** Total Total 7.21 7.21 1.07 5.18 5.18 4th Floor 1.07 20.73 1.97 3.04 9.7 14.88 13.52 **3rd Floor** 34.21 2nd Floor 13.48 1.98 5.02 9.67 24.55 Wall 2 Wall 5 Wall 8 **Shear Force Total Shear Force Total Shear Force Total** 2.1 1.07 4th Floor 6.01 6.01 2.1 1.07 11.27 17.28 3.94 6.04 1.97 3.04 **3rd Floor** 11.23 28.51 3.93 9.97 1.98 5.02 2nd Floor Wall 3 Wall 6 **Shear Force Shear Force Total** Total 2.56 6.04 6.04 4th Floor 2.56 7.35 11.32 17.36 **3rd Floor** 4.79 11.28 28.64 2nd Floor 4.77 12.12

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions

Samuel Avila Structural Option



Post-Tensioned One-Way Slab

	Direction	# of walls	Thickness (in)	Reinforcement
Shear 1	N/S	1	10	5 @ 24"
Shear 2	N/S	1	10	5 @ 24"
Shear 3	N/S	1	10	5 @ 24"
Shear 4	N/S	6	12	5 @ 24"
Shear 5	E/W	1	10	5 @ 24"
Shear 6	E/W	1	10	5 @ 24"
Shear 7	E/W	1	10	5 @ 24"
Shear 8	E/W	6	12	5 @ 24"

Shear Wall Results

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions



Mechanical Analysis

Existing System

Water Source Heat Pump (WSHP) System With 2 Heat Pumps on the Ground Floor and 11 Exhaust Fans

Proposed System

Energy Recovery Ventilator (ERV) System (50% Better Efficiency than existing system) With Both the Heat Pumps and Ventilators located on the Top Floor

Is This A Feasible Alternative to Reduce HVAC Operational Costs??

Introduction

Existing System

Problem

Proposal

Structural System Redesign


Breath work

Conclusions

Samuel Avila Structural Option



Mechanical Analysis




Structural Option

Advisor: Dr. Thomas Boothby



Mechanical Analysis




Samuel Avila Structural Option

Advisor: Dr. Thomas Boothby



Mechanical Analysis




Samuel Avila Structural Option

Advisor: Dr. Thomas Boothby



Mechanical Analysis



Samuel Avila Structural Option



Mechanical Analysis

RS MEANS

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions

Cost of Running Exhaust Fans è \$400 per 320 cfm Total Savings from Eliminating Fans è \$3600 Cost of ERV Unit + Installation è \$3200 Total Costs of Installing ERV Units è \$6400 Net Loss after ERV Installation è \$2800

Sensible Heat

q = 1.08 x flow rate (cfm) x • T = 62,000 Btu/hr from exhaust è 31,000 Btu/hr savings



Mechanical Analysis

Assumptions

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions

Assumptions
Average Outdoor Temperature During the Summer in Orlando, Florida è 90° F
Desired Indoor Temperature è 70° F
It is 90° F For Approximately 150 Days Per Year and Approximately 8 Hours Per Day
Cost in Orlando, Florida è \$0.10 Per KW
Solution
Amount Saved è \$0.26 per hour

Time until profit made è 10,800 operating hours

è 9-10 years



Acoustical Analysis

Part I: IBC 2000 F	Requirements
--------------------	---------------------

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions

SIC _{minin}	$_{num} = 50 \text{ dB}$
	_m = 50 dB

Surface	Materials	STC	ICC	
Walls	8" cmu blocks	58	N/A	
Floor/Ceiling	5" concrete slab	48	25	
Interior wall		50	N/A	
intenor wall	2x4 steel studs 16" o.c. w/ 5/8" gypsum board both sides	52	N/A	



Acoustical Analysis

 $STC_{minimum} = 50 \text{ dB}$

 $IIC_{minimum} = 50 \text{ dB}$

Part I: IBC 2000 F	Requirements
--------------------	---------------------

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions

Surface	Materials	STC	ICC	
Walls	8" cmu blocks	58	N/A	
Floor/Ceiling	5" concrete slab	48	25	
Interior wall	2x4 steel studs 16" o.c. w/ 5/8" gypsum board both sides	52	N/A	

Not OK

Samuel Avila Structural Option



Acoustical Analysis

Solution

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions

ACOUSTIK Acoustic Subflooring 2'0" x 2'0" Panels Thickness = 5/16"

Increases STC è 65 dB Increases IIC è 55 dB



Samuel Avila Structural Option



Acoustical Analysis

Part II: AHU Check

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions

SA x • = a NR = L1 – L2 TL_{actual} = NR – 10(log(a/S)) where: SA = total surface area of the apartment (ft²) • = absorption coefficient a = absorption (sabins) NR = Noise Criteria S = surface area of common wall (ft²)

L_{source} Calculated From Acoustics Program TAP

RC = 30 (for apartments)



Acoustical Analysis

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions

Frequency (Hz)	L _{source} (dB)	RC-value	TL _{required}
125	86	45	41
250	85	30	55
500	84	35	49
1000	83	30	53
2000	82	25	57
4000	80	20	60

Frequency (Hz)	• (sabins)	S (ft²)	TL _{actual}
125	106.25	216	44
250	70.08	216	60
500	85.44	216	53
1000	94.08	216	57
2000	111.36	216	60
4000	96	216	64

TL_{actual} • TL_{required}



Acoustical Analysis

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions

Frequency (Hz)	L _{source} (dB)	RC-value	TL _{required}
125	86	45	41
250	85	30	55
500	84	35	49
1000	83	30	53
2000	82	25	57
4000	80	20	60

Frequency (Hz)	• (sabins)	S (ft²)	TL _{actual}
125	106.25	216	44
250	70.08	216	60
500	85.44	216	53
1000	94.08	216	57
2000	111.36	216	60
4000	96	216	64

TL_{actual} • TL_{required}

OK



Conclusion

<u>Structural</u>

Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions

Redesign of slab allowed for longer spans increasing each unit's flexibility while minimizing the slab thickness Redesign of shear walls to carry excess load successful

Mechanical

Proposed ERV system will provide greater savings than existing system after about 10 years

Acoustical

Using an acoustic subflooring helps new system meet IBC 2000 requirements

Rooms adjacent to mechanical rooms are sufficient to resist noise from air handling units



Acknowledgements

AE Faculty and Staff

Introduction

Problem

Proposal

Redesign

Breath work

Conclusions

Existing System

Structural System

TLC Engineering

better engineers.

For providing the plans for my building and answering all my questions throughout the year

For all the effort, time, and input given to help us become

Dr. Maria Lopez de Murphy

For all the time devoted to help me understand posttensioned systems better.

My Family & Friends

For always believing in me and walking with me every step of the way

My wife, Franchesca

For your tireless love and confidence in me

Samuel Avila Structural Option



Introduction

Existing System

Problem

Proposal

Structural System Redesign

Breath work

Conclusions



Samuel Avila Structural Option