

EXECUTIVE SUMMARY JW MARRIOTT, GRAND RAPIDS, MI DECEMBER 15, 2006

GREG KOCHALSKI Structural Advisor: Boothby

Building Description:

The JW Marriott is a 24 story hotel currently under construction in Grand Rapids. The 376,000 square foot hotel will offer over 300 guest rooms. With multiple accommodations including a business center, restaurant, 24 hour concierge the JW Marriott will match the service of any hotel in the area. A helipad, heated driveway and sidewalks, and an adjacent parking deck with a Sky



Bridge give distinctive touches to the hotel. The unique elliptical shape will create a strong presence in the otherwise conservative Grand Rapids skyline. Reflective glass cladding helps to accentuate its place along the Grand River. The JW Marriott will welcome its first guests in the fall of 2007.

Proposal:

Given its location the JW Marriott is not likely to see high seismic loads throughout its lifetime. If the owner wished to use the same design in Monterey, California, a seismically active location, the design will need to change. I propose to redesign the structure to withstand the forces conforming of the new seismically active site.

Solution:

The primary focus will be to keep as many characteristics the same for the new JW Marriott. I will redesign the JW Marriott in accordance with California state codes and provisions. In doing so I will pay close attention to the floor, framing, and lateral force systems. These systems will need designed with higher capacities to withstand seismic forces.

Breadth Topics:

Along with the redesign of the building's structural system I plan to investigate the effects on the construction and mechanical system. The design must be done in a manner that concrete may be poured and assured of proper consolidation. If necessary I will investigate alternative concrete mix designs. Higher cooling loads and lower heating loads will warrant a new air to air handling unit for the building. I will determine the current and new heating loads then chose an AHU suitable for Monterey conditions.

TABLE OF CONTENTS

Introduction	1
Background	1
Problem Statement	3
Problem Solution	3
Solution Method	4
Breath Options	5
Tools and Tasks	5
Time Table	6
Appendix	8

INTRODUCTION

The JW Marriott is a 24 story hotel currently under construction in Grand Rapids. The 376,000 square foot hotel will offer over 300 guest rooms. With multiple accommodations including a business center, restaurant, 24 hour concierge the JW Marriott will match the service of any hotel in the area. The unique elliptical shape will create a strong presence in the otherwise conservative Grand Rapids skyline. Reflective glass cladding helps to accentuate its place along the Grand River.



The hotel is being constructed under the 2003 Michigan Building Code. The 2003 MBC is an adoption of the 2003 IBC with state amendments. The building rises approximately 256 ft above grade. A helipad, heated driveway and sidewalks, and an adjacent parking deck with Sky Bridge give distinctive touches to the hotel. The architect and structural engineer determined that the absence of perimeter columns would have large aesthetic benefits with minimal structural efficiency penalties. Wall-columns were used instead of large circular perimeter columns. These members typically 10 in wide and 11 ft long are hidden within partitions between guest rooms.

BACKGROUND

Structural Codes:

- Building Code Michigan Building Code 2003. The 2003 Michigan Building Code is an adoption of the IBC 2003 with state amendments.
- *Structural Concrete* ACI 318-2002. Building Code Requirements for Structural Concrete.
- Concrete Masonry ACI 530-1999. Building Code Requirements for Masonry Structures.
- Structural Steel LRFD Specification for Structural Steel Buildings, 2nd Edition. AISC.

Foundation:

The foundation of the JW Marriott consists of multiple parts. A slab on grade covers the entire basement with 6 inches of 4000 psi concrete reinforced with WWF and 10 inches

of 4000 psi concrete reinforced with 4#12 bars each way in the loading dock area. Grade beams travel between the building elevator core pile caps. The grade beams range in size from 16-28 inches wide by 42-48 inches in height. All grade beams are 6000 psi concrete reinforced top and bottom. Along the perimeter of the tower there are 21 piles that consist of (4-7) 200 ton micropiles. Each micropile drives 19' into the ground. In the elevator core there is a cache of micropiles, (94) 200 ton. Just outside the elevator core there are two groups of 8 micropiles, one of each side of the core in the North-South direction.

Framing System:

The repetitive tower framing plan offers a distinct advantage to the structural engineer and general contractor. The typical framing plans take affect from floor 5 through 23. On the first and second floor there are 21 reinforced concrete columns, 24 inches in diameter. The concrete in the columns change from 10 ksi to 8 ksi to 6 ksi at the sixth and fourteenth floors, respectively. Above the fifth floor the number of circular columns is reduced to four. In the guest rooms, columns are replaced by a series of 10 inch thick wall-columns to maximize views. The elevator core offers support for the interior of the structure.

Floor System:

The existing floor system of the JW is a oneway reinforced concrete flat plate from floors 5 through 22. The slab is 7.5 inches thick and uses 5000 psi strength concrete (unless otherwise noted). Fourteen openings in the slab, located in the main corridor, allow for mechanical duct access. The overall shallow depth of the system permits greater flexibility for the architect's interior design. Throughout the guest levels code specifies 40 psf live load. The size of the typical bay is a trapezoid with vertical lengths 10'-7" and increasing to 17'-9" and a horizontal length of 35'-3".

Lateral System:

Concrete shear walls and will serve as the primary lateral force resistance. Located within the elevator core, the walls will span from the basement to the helipad. Two major pairs span in each direction (two 25'-6" walls in the East-West direction and in the North-South direction a 35' and a 10'-7" wall). All shear walls are 12 inches thick.




Figure 1. Typical Bay

Additional lateral support is gained from the wall-columns placed along the exterior of the JW. These walls are typically 11'-8" wide and 10" wide. The wall-columns are staggered at angles ranging from approximately 45-78 degrees from vertical. The concrete used in both shear walls and wall-columns vary with height above grade from 6 to 10 ksi.

PROBLEM STATEMENT

The JW Marriott has been designed with great care to optimize all building systems in conjunction with the architect's difficult plan. The structural system used has proven to be the best choice based on research done in technical reports 2 and 3. In technical report 2, the flat plate framing system bested all alternatives keeping with industry standards for mid rise residential structures. The lateral system proved to be sufficient when analyzed and compared to ASCE7-02 for wind and seismic loading in technical report 3. The JW Marriott performs sufficiently for low seismic activity. However, if the owner wished to use the same unique building design in Monterey, California, an area of high seismic activity, the structural system would certainly need to be changed.

PROBLEM SOLUTION

Industry standards have proven that the most efficient material for mid rise residential structures is concrete.

Therefore, the floor system should remain a flat plate system to optimize material and labor costs. Attention must be paid to joints and interfaces connecting columns, beams, and slabs together to assure proper rotational capability. The current 7.5 in flat plate system will be redesigned if the current thickness and concrete slab strength (5000 psi) are found to be insufficient for the new loading conditions and code requirements.

Shear wall lateral systems have proven to be reliable under high seismic activity. With this in mind the lateral system will be redesigned to withstand much larger seismic forces in accordance with the appropriate codes.

SOLUTION METHOD

Floor System:

The flat plate floor system will be designed in accordance with ACI 318 Chapter 21 Section 21.11 with special checks for deformation capability. Computer modeling with ETABS will be done to simulate the floor system and then compared to manual findings. The live loads shall be in accordance with ASCE7-05. Pattern loadings will be checked for full live load on all spans, full and half live load on adjacent spans,




Figure 2. Flat Plate System


and ³/₄ full loads and no load on adjacent spans will be investigated.

Lateral System:

The lateral system will be analyzed for the wind and seismic loading conditions set forth in ACI 318-05 Chapter 21 Section 21.7 with special checks for deformation capability. All applicable loading combinations will be investigated per ASCE7-05. The loading data will then be placed into ETABS and analyzed to determine the forces within each wall. The computer model forces will be compared to those found by hand analysis. The wall will then be designed based on the worst case loading combination of forces.

Note: For both systems, in addition to what has been mentioned above the following topics will need to be considered.

- Accidental torsion and amplification
- o Redundancy Factor
- o Overstrength Factor
- Deflection and amplification Factor
- Vertical Earthquake Effects



BREATH OPTIONS

Redesigning the JW Marriott for a high seismic zone, Monterey, California, will offer many opportunities for breadth study. I will focus on two major areas of study, construction management and mechanical systems.

First, construction must be considered because joints connecting building elements are likely to endure rebar congestion. The design must be done in a manner that concrete may be fittingly poured and reach proper consolidation. If necessary I will investigate alternative concrete mix designs to solve any dilemmas. 3-D AutoCad drawings will be made to show examples of critical joints and the rebar inside them.

Second, if the building is to be built in Monterey the mechanical system will be subject to change as well. Higher cooling loads and lower heating loads will warrant a new air to air heat exchanger. For instance, average January temperatures differ by 31 degrees between Grand Rapids and Monterey. With this in mind I will determine the current heating loads, new heating loads, and then chose a handler suitable for Monterey.

TASKS AND TOOLS

Phase 1. Flat Plate Floor System.

Task 1. Determine superimposed loads

- o Determine dead loads from architectural and structural drawings
- Determine live loads in accordance with ASCE7-05
- Task 2. Establish trial member sizes
 - Determine minimum slab thickness from ACI 318 Ch. 9 Sect 9.5.3 to control deflections
 - o Consult PCA Simplified Design publications
- Task 3. Refine Floor System
 - Use SEAOC Seismic Design Manual
 - Verify findings with ACI 318-05 Chapter 21 Sect. 21.11 with special checks for deformation capability
- Sub-Task 7. Determine Constructability of Members
 - o Investigate beam/column/slab/shear wall joints for rebar congestion
 - Determine if alternate concrete mix designs necessary for proper consolidation, if so, design new mix
- Phase 2. Main Lateral Force Resisting System.
 - Task 4. Verify wind and seismic loads
 - Use ASCE7-05 to determine wind and seismic loading
 - Task 5. Determine Loads on individual structural members
 - Use ETABS computer modeling with previously determined lateral loads
 - Use manual and spreadsheet analysis (in part from technical report 3) to find loads to individual members
 - o Compare computer to manual findings

- Task 6. Design Lateral System Members
 - Use SEAOC Seismic Design Manual and PCA notes on ACI 318 to establish trial sizes
 - Design concrete sections in accordance with ACI 318-05 Ch. 21 Sect. 21.7 with special checks for deformation capability
 - Design reinforcement and layout in accordance with ACI 318
- Sub-Task 7. Determine constructability of members
 - o Investigate beam/column/slab/shear wall joints for rebar congestion
 - Determine if alternate concrete mix designs necessary for proper consolidation, if so design new mix
- Phase 3. Breath Studies.
 - Task 7. Determine constructability of members
 - Construct 3-D AutoCad representations of typical joints
 - Task 8. Design mechanical air handling unit
 - o Determine Grand Rapids and Monterey cooling and heating loads
 - o Select new air to air heat exchanger


TIME TABLE

	Week 1	Week 2	Week 3	Week 4	Week 5	Week 6	Week 7	Week 8
Task 1								
Task 2								
Task 3								
Task 4								
Task 5								
Task 6								
Task 7								
Task 8								
Compile Final Report								
Create Final Presentation								
Present to Faculty								


	Week 10	Week 11	Week 12	Week 13	Week 14	Week 15	Week 16	Week 17
Task 1	10		12	15	17	15	10	17
Task 2								
Task 3								
Task 4								
Task 5								
Task 6								
Task 7								
Task 8								
Compile Final Report								
Create Final Presentation								
Present to Faculty					· ·			

APPENDIX: FLOOR PLANS






	$= \frac{3}{2} + $	FOR SLAB INFORMATION AT INFORMATION AT SEE NOTE 2 ON S201
Image: construction and permit 17 02 DEC 05 16 28 OCT 05 17 02 DEC 05 18 20 OCT 05 19 20 ULV 05 10 20 ULV 05 11 02 DEC 05 12 20 OCT 05 11 02 DEC 05 11 02 DEC 05 12 12 OCT 05 12 12 OCT 05 12 12 OCT 05 13 20 ULV 05 14 12 OCT 05 15 21 OCT 05 15 21 OCT 05 16 20 DEC 05 17 02 DEC 05 18 EXEX PROPERT ELVATION + 0.0" = GRAND RAPES + 61.0" 10 202 A LOUAN CAPRE DETECH OFFICH OFFICH PROPERT ELVATION + 0.0" = GRAND RAPES + 61.0" 14 14 PROPERT INSTANCES + 61.0" 15 10 OCT OUAN CAPRE DETECH DETECH OFFICH PROPERT INSTANCES - 61.0" 16 12 OCT OUT OUAN CAPRE DETECH DETECH OUTSCH O		



EFERENCE: . SEE DRAWING SOO1 FOR GENERAL NOTES. . SEE DRAWING S400 FOR CONCRETE COLUMN DETAILS. . SEE DRAWINGS S401 & S402 FOR CONCRETE SLAB DETAILS. . SEE DRAWINGS S403 & S404 FOR CONCRETE SLAB DETAILS. . SEE DRAWINGS S405 & S405A FOR CONCRETE BEAM DETAILS.	The second sec	RIA	TYPICAL ALONG PERIMETER TO RADUAL COLLIAN LINES REPERVICULAR	KSH-Z KSH-Z 6"W × 8"H CURB SEE TYPICAL CURB SEE TYPICAL CURB DETAIL FOR REINF TO RADIAL COLUMN LINES, UON	BS In the transmission of	
Image: Note of the state of the st					Tel: 212.888.7663 www.bbg-bbgm.com THORNTON-TOMASETTI GROUP Structural Engineer 14 East Jackson Bivd, Suite 1100 Chicago, IL 60604-2209 Tel: 312.596.2000 www.theTigroup.com Program Manager 226 West Liberty Street Ann Arbor, MI 48104 Tel: 734-769-0530 www.pmaconsultants.com COSENITIN ASSOCIATES MEP & FP Engineer One East Wacker Drive Chicago, IL 60601 Tel: 312-670-1800 www.cosentini-iL.com FISHBECK, THOMPSON, CARR HUBER, INC. Civil / Environmental Engineer 1515 Arboretum Drive, SE Grand Rapids, Michigan 49546 Tel: 616-575-3824 www.tchicigan 49546 Tel: 616-575-3824 www.tchicago, IL 60604 Tel: 312-427-2888 www.dwplid.com	Atter, Inc. HP3, LC Atter, Inc. HP3, LC Tel: 616-787-6546 www.lofan.com Tel: 312,356,0600 www.lofan.com BETA DESIGN GROUP Associate Activited Tol: 616-235-620 www.betadesign.com BERNANG REAR ADDRACH IN ASSO Second Activited Standard Rapids, MI 49503 Second Activited Tel: 312,356,0600 www.lofan.com












































soot for general notes. Soot for concrete column details. Saot & Saot & Saot For concrete slab details. Saot & Saota for concrete beam details.	RTE ISSUE	R
Image: state		




REFERENCE: 1. SEE DRAWING S001 FOR GENERAL NOTES. 2. SEE DRAWING S400 FOR CONCRETE COLUMN DETAILS. 3. SEE DRAWINGS S401 & S402 FOR CONCRETE WALL DETAILS. 5. SEE DRAWINGS S403 & S404 FOR CONCRETE SLAB DETAILS. 5. SEE DRAWINGS S405 & S405A FOR CONCRETE BEAM DETAILS.	SHORING NOTE: WALL COLUMN MUST BE SHORED SUAB HAS BEEN REMOVED REMOVED REAL	REINFORCEMENT LAYOUT AND BEAM LAYOUT REINFORCEMENT LAYOUT BEAM LAYOUT	R R
Image: market interview Image: market interview Image: market interview Image: market interview <td></td> <td></td> <td></td>			




	5x3 1/2x5/1 CING AT TOP INECTIONS TO INECTIONS TO	26				RUSS T2 TOP CHORD (SLOPING)					6	
	5/16 LLBB HORIZONTAL OP CHORD, TYPICAL TO BE DESIGNED FOR AL LOAD = 49 KIPS	WORK LINE OF TRUSS PANEL POINT SEE TRUSS ELEVATION	WORK LINE OF TRUSS PANEL POINT SEE TRUSS ELEVATION 34	WORK LINE OF TRUSS PANEL POINT SEE TRUSS ELEVATION	WORK LINE OF TRUSS PANEL POINT SEE TRUSS ELEVATION	WORK LINE OF TRUSS PANEL POINT SEE TRUSS ELEVATION 32'-0" 101'-4"	WORK LINE OF TRUSS PANEL POINT SEE TRUSS ELEVATION	WORK LINE OF TRUSS PANEL POINT SEE TRUSS ELEVATION 34'-8" B.6	1'-4" WORK LINE OF TRUSS PANEL POINT SEE TRUSS ELEVATION			
Image: Signed Field Signed										COSENTINTASSOCIATES MEP & FP Engineer One East Wacker Drive Chicago, IL 60601 Tel: 312-670-1800 www.cosentini-il.com FISHBECK, THOMPSON, CARR HUBER, INC. Civil / Environmental Engineer 1515 Arboretum Drive, SE Grand Rapids, Michigan 49546 Tel: 616-575-3824 www.ftch.com DANIEL WEINBACH & PARTNERS, LTD. Landscape Architect 53 W. Jackson Blvd., Suite 1850 Chicago, IL 60604 Tel: 312-427-2888 www.dwpltd.com	Associate Architect 70 Ionia SW, Suite 400 Grand Rapids, MI 49503 tel. 616-235-6220 www.betadesign.com BRENNAN BEER GORMAN MONK Interior Architect 515 Madison Avenue New York, NY 10022 Tel: 212.888.7663 www.bbg-bbgm.com THORNTON-TOMASETTI GROUP Structural Engineer 14 East Jackson Blvd, Suite 1100 Chicago, IL 60604-2209 Tel: 312.596.2000 www.theTTgroup.com PMA CONSULTANTS Program Manager 226 West Liberty Street Ann Arbor, MI 48104 Tel: 734-769-0530 www.pmaconsultants.com	Intervention of the i




10 10 10 10 10 10 10 10 10 10	Image: Single state W24x68 (28) 10" 97 00 yr 26'-4" 20'-8" 5'-8" 20'-8"	$ \begin{array}{c} $	TRUSS T2 (BOTTOM CHORD) TRUSS PANEL POINT SEE TRUSS PANEL POINT S	WI4x38 (16) WI4x38 (16) WI4x38 (16) WI4x38 (16) WI4x38 (16) WI4x38 (16) SEE TRUSS PANEL POINT RUSS PANEL POINT RUSS PANEL POINT SEE TRUSS ELEVATION 34'-8" BG	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
ECT ELEVATION	Image: Second Secon			MEP & FP Engineer One East Wacker Drive Chicago, IL 60601 Tel: 312-670-1800 www.cosentini-il.com FISHBECK, THOMPSON, CARR HUBER, INC. Civil / Environmental Engineer 1515 Arboretum Drive, SE Grand Rapids, Michigan 49546 Tel: 616-575-3824 www.tch.com DANIEL WEINBACH & PARTNERS, LTD. Ladscape Achited 53 W. Jackson Bird., Suite 1850 Chicago, IL 60604 Tel: 312-427-2888 www.dwpltd.com	Index of the end the end the end the end of the end the end of the end




OF ELEVATOR REQUIREMENTS. TOR MANUFACTURER.	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	$\frac{226 (14)}{9}$ $\frac{14}{9}$ $\frac{1}{9}$ $\frac{1}{9$
	F E3	C B.6 B.3	(\mathbf{B})
15 24 OCT 05 TOWER CONCRETE BID PACKAGE A 23 SEPT 05 BID ADDENUM #4 -STRUCTURAL STEEL & FOUNDATIONS 5 20 MAY 05 REVISED DESIGN DEVELOPMENT 1 10 DEC 04 SCHENDIN EVELOPMENT 1 10 DEC 04 SCHENATIC DESIGN DEVELOPMENT 10 DEC 04 SCHENATIC DESIGN DEVELOPMENT DESIGN DEVELOPMENT 10 DEC 04 SCHENATIC DESIGN DEVELOPMENT DESIGN DEVELOPMENT SECOND MEZANING PLAN RAND RAPIDS + \$15.0" © 2004 LOHAN CAPEULE DETTSCH urbited SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE: SALE:	Image: Note of the second s		



T OF ELEVATOR RATION OF POSITS R REQUIREMENTS. WATOR WANUFACTURER.	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	E.7 W24x68 (14) W14x48 W14x	WORK S5	Image: Non-State Image: Non-State Image: Non-State OOR TRUSS T3 (c=1") Image: Non-State Image: Non-State Image: Non-State I	$\begin{array}{c} 1 - 10^{\circ} \\ 20' - 4^{\circ} \\ \end{array}$
ECT ELEVATION	Image: Sector of the sector				



10 10 14 14-3/4*ø A325 BOLTS 14-3/4*ø A325 BOLT	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	20'-4" 32'-0" 210'-0" (C) (B)	(\mathbf{B})
e.o' = G G FOUND	Image: State of the state o		



The rest of the second	F.1 F.1 F.1 F.1 F.1 F.1 F.1 F.1 F.1 F.1	PC-J PC-J	32 ² -0" 210'-0"	B6 B7 B7 B7 B7 B7 B7 B7 B7 B7 B7 B7 B7 B7	
FOUNDATION AN REVISED DESIGN DESIGN DEVELO SCHEMATIC DES SCHEMATIC DES BASE BASE RAND R.	Image: Section 2.1 ADDENDUM #6 Image: Section 2.1 ADDENDUM #6 Image: Section 2.1 Issued for construction and permit Image: Section 2.1 Issued for construction and permit Image: Section 2.1 Image: Section 2.1 Image: Section 2.1 Image: Section 2.1			14 East Jackson Bird, Suile 110 Chicago, IL 60604-2209 Tei: 312.596.2000 www.theTTgroup.com Program Manager 226 West:Libery Street. Ann Ator, M 4010 Tei: 734-769-0530 www.pmaconsultants.com MEP & FP Engineer Tei: 312-670-1800 www.cosentini-it.com FISHBECK, THOMPSON, CARR HUBER, INC. Civil / Environmental Engineer 1515 Arboretum Drive, SE Grand Rapids, Michigan 4954 Tei: 616-675-324 www.that.com DANIEL WEINBACH & PARTINERS, LTD. Landscape Archited 31 W. Jackson Bird, Suile 1860 Chicago, IL 60604 Tei: 312-427-2888 www.dwpltd.com	India A series a