John P. Mulhern Lighting/Electrical



New Jersey Center For Science, Technology, and Mathematics Education

Project Team

Owner: Kean University

Architect + MEP Cannon Design, Inc.

Structural: Schoor Depalma Engineers &

Consultants

Civil Engineer: K.S. Engineers, P.C.

CM: Provided by University

GC: Terminal Construction

Corporation



General Building Information

Address: Union, NJ

Size: 6 Stories, 117,000 SF

Construction Dates: Groundbreaking September

2008

Delivery Method: Design-Bid-Build

Overall Cost: \$45,000,000

Electrical

- Primary service provided by PSE&G at 13.2 KV
- ■2500 KVA transformer in main electrical room which steps down secondary service to 480/277V, 3¢, 4W
- ■500 KW rated diesel generator for emergency
- ■3rd to 6th floor fed by 1200A bus duct at 480V and is stepped down to 208/120V with a transformer on each floor and distribution panel

Structural

- Structural steel building
- System of spread footing ranging from 4' X 4' to 15' X 15'
- •5" slab on grade reinforced with 6x6 W2.0 X 2.0 welded wire fabric
- ■Typical bay is 21' X 37'8"
- ■3" 20 gauge composite galvanized metal floor deck with
- 3 ¼" lightweight concrete topping

Lighting

- Linear fluorescent luminaire with a direct distribution is uutilized most throughout the building
- There are also many square downlights throughout the
- building
- Many fixtures have dimming capabilities
- •There are many spaces with two sets of luminaires, ones with cool CCT's and ones with warm CCT's

Architectural

- Glass curtain wall with three different types of glass for most of façade makes it very transparent
- Double height lobby
- Partial green roof above auditorium
- Some features include executive center, 3D cave, exhibition space, and 300 person auditorium
- Roof system is composite metal deck with concrete

topping with 4" rigid insulation

Mechanical

- 6 air handling units serve the building while one is is reserved for future restaurant tenant
- ■300 ton rated cooling tower
- Geothermal system of 131 boreholes dug 500' down and spaced 20' apart
- VAV system utilized throughout building

http://www.engr.psu.edu/ae/thesis/portfolios/2009/jpm5006/