

Buckhorn Medical Office Building

Shane Boyer
Construction Management



AE Senior Thesis 2010

Buckhorn Medical Office Building


240 Mall Boulevard
Bloomsburg, PA 17815

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions



Aerial view of the project site

Project Overview

Client Information

- Owner: Geisinger Health System
- Architect: Borton-Lawson Architects
- Construction Manager: Alexander Building Construction

Project Location

- 240 Mall Boulevard, Bloomsburg, PA
- 2 Miles from the Buckhorn I-80 Exit



GEISINGER

ALEXANDER

Project Background

Outline

- Project Overview
- **Project Background**
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions


- **Building Function:** Medical Office Building
- **Site Size:** 530,300 SF
- **Building Size:** 83,245 SF
- **Construction Cost:** \$11.7 million
- **Construction Period:** December 2007 – October 2009
- **Delivery Method:** Design-Bid-Build with CM-at-Risk



Rendered view of the project site

Outline

- Project Overview
- **Project Background**
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions



Structural system modeled in Revit



Mechanical room modeled in Revit MEP

Project Background

Architecture

- Aluminum panel curtain wall
- Employee cafeteria
- LEED Silver rating

Structure

- Structural steel building with spread footings

Mechanical

- Water-cooled heat pump system

Lighting/Electrical

- Typical 480Y/277V power system for commercial office
- Typical 277V fluorescent 2'x4' fixtures
- 125kVA on-site emergency diesel generator



Various metal panels in curtain wall system



Render of cafeteria using Revit and 3D Studio

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions




Thesis Theme

Building Information Modeling (BIM)

Owner's demands for BIM

Contractor's uses for BIM

“How do we effectively use BIM?”



Re-developing the Curtain Wall System

ANALYSIS 1

Re-developing the Curtain Wall System

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using

BIM

- Conclusions
- Questions

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions



Curtain wall mock-up panel

Current System

- Current façade is an aluminum metal panel system
- 4 different panel designs used in curtain wall construction
- Construction consists of metal studs with insulating board, plywood sheathing, and metal panels



Current metal panel curtain wall system

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions



Construction of the curtain wall system

The Problem

- Material availability by Marcon Roofing
 - Delays due to supplier backlog of work
- Damaged panels upon arrival on-site
- Constructability challenges
 - Snap-on cover strips from a 3rd party manufacturer
- Cost implications
 - Expensive material costs



Re-developing the Curtain Wall System

The Result

- Multiple delays in the project schedule
- Final completion date pushed back
- Poor image of the construction manager

ALEXANDER



Missing panels on front façade of building

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions

Re-developing the Curtain Wall System

The Solution: Pre-cast concrete

- Extremely durable for climate
- Can be cast to resemble architectural features
- Color matching using dye ad-mixtures
- Increased fire protection
- Low reflectance of concrete to fit into surroundings



Exterior texturing to simulate aluminum panels



Exterior texturing to simulate aluminum panels

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions



High's facilities – Denver, PA

Re-developing the Curtain Wall System

The Solution: Pre-cast concrete

- Supplier: High Concrete
 - No delays in schedule (removed from the critical path)
 - 65-day savings
- Cost savings
 - Revit Quantity Schedules used for SF take-offs
 - Aluminum costs vs. *RS Means* pre-cast concrete costs
- Constructability
 - Snap-on cover plates vs. caulking

Architectural Pre-Cast Concrete Panel System			
Total SF of Wall:		24862.03	
Summary	Cost Per Square Foot(\$/SF)	Total Cost(\$)	Percentage(%)
Material Total	\$19.95	\$495,997.50	74.27
Labor Total	\$4.30	\$106,906.73	16.01
Equipment Total	\$2.61	\$64,889.90	9.72
Total Structural Estimate:	\$26.86	\$667,794.13	100.00

Architectural Panel System Cost Comparison		
Total SF of Wall:		24862.03
Summary	Cost Per Square Foot(\$/SF)	Total Cost(\$)
Aluminum Panel System	\$34.38	\$854,808.00
Pre-cast Panel System	\$26.86	\$667,794.13
Cost Difference:	\$7.52	\$187,013.87
General Conditions Savings	Cost Per Day(\$/Day)	Total Cost(\$)
65 Days	\$1,983.42	\$128,922.30
Total Cost Savings:		\$315,936.17

Developing a Sustainable Photovoltaic Panel System

ANALYSIS 2

Developing a Sustainable Photovoltaic Panel System

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- **Electrical Breadth**
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions



Developing a Sustainable Photovoltaic Panel System

Background

- Hundreds of high-energy consumption devices
- LEED Silver Rating
 - Construction practices and materials, NOT DESIGN
- Geisinger is a leader in “green” medical facility construction



Geisinger's Headquarters – Danville, PA



Gray's Woods – LEED Gold Certified

Outline


- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions

Objective


- Propose a grid-tied photovoltaic (PV) array that will provide an energy reduction without much physical impact on the architectural aesthetics of the building.

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions



Sun Path Chart for Bloomsburg, PA




World Insolation Map

Developing a Sustainable Photovoltaic Panel System

Solar Analysis

- Found peak hours of sun exposure based on location (9am-3pm)
- Used Revit model to perform shadow simulations
 - Created exact shadows based on latitude & longitude

Revit Solar Studies



Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions

Developing a Sustainable Photovoltaic Panel System

Determining the Site Lighting Load

- Offset the energy load of the site lighting using PV panel array
- Use panel board schedules to determine lighting load
 - Total load: ~11kW

PANEL LP SECTION 1						SQUARE D POWERLINK G3					
LOCATION OF PANEL		ELEC 132	DOUBLE PANELBOARD			VOLTAGE	277/480 VOLT, 3PH, 4 WIRE				
PANEL FEEDERS FROM		MDP	FEED-THRU LUGS			SCCR	25,000 MINIMUM				
# OF SPACES		66	PH LOAD (KVA) x 1.25			TRIM	SURFACE				
CONDUIT SIZE		2"	A 21.9 27			FEED	BOTTOM				
PHASE WIRE (TAP)		#1	B 24.9 31			MAIN	200 AMP				
NEUTRAL WIRE		#1	C 19.8 25			BUSS	225 AMP CU FEED THRU LUGS				
GROUND WIRE		#8				BRKR	BOLT ON				
#	CIRCUIT DESIGNATION	LOAD (VA)	CB	PHASE	CB	LOAD (VA)	CIRCUIT DESIGNATION	#			
1	RM 105 A CENTER LAMP	352	20	A	20	1024	RM 105 A OUTER LAMPS	2			
3	RM 105 B CENTER LAMP	992	20	B	20	2304	RM 105 B OUTER LAMPS	4			
5	RM 105 C CENTER LAMP	960	20	C	20	2304	RM 105 C OUTER LAMPS	6			
7	RM 109A D CENTER LAMP	256	20	A	20	640	RM 109A D OUTER LAMPS	8			
9	RM 109A E CENTER LAMP	256	20	B	20	640	RM 109A E OUTER LAMPS	10			
11	RM 109B F CENTER LAMP	288	20	C	20	640	RM 109B F OUTER LAMPS	12			
13	RM 109B G CENTER LAMP	224	20	A	20	640	RM 109B G OUTER LAMPS	14			
15	RM 109B H CENTER LAMP	273	20	B	20	644	RM 109B H OUTER LAMPS	16			
17	113 CENTER LAMP	768	20	C	20	1792	113 OUTER LAMPS	18			
19	VEST 100, LOBBY 101, CORRIDOR LTG	1698	20	A	20	2072	113 OUTER LAMPS	20			
21	LTG 114-116 129-134 121 122	3485	20	B	20	1164	LTG 106-108 119 118 117 103 104	22			
23	SITE LTG	1340	20	C	20	400	EXTERIOR BLDG LTG	24			
25	SITE LTG	1340	20	A	20	2323	SITE LTG	26			
27	SITE LTG	1605	20	B	20	2323	SITE LTG	28			
29	SITE RECEIPT	1605	20	C	20	2250	SITE RECEIPT	30			
31	SITE RECEIPT	3000	20	A	20	2250	SITE RECEIPT	32			
33	SITE RECEIPT	3000	20	B	20	2250	SITE RECEIPT	34			
35	SITE RECEIPT	2250	20	C	20	2250	SITE RECEIPT	36			
37	SITE RECEIPT	2250	20	A	20	3000	SITE RECEIPT	38			
39	SITE RECEIPT	3000	20	B	20	3000	SITE RECEIPT	40			
41	SITE RECEIPT	3000	20	C	20*		EM RELAY VOLT MONITOR	42			

ALL BREAKERS SHALL BE MOTORIZED UNLESS OTHERWISE NOTED. *NON-MOTORIZED BREAKER

SECTION 2 SHALL BE 225AMP, 277/480VOLT 3PH 4W 24 CIRCUIT SLAVE PANEL WITH(18) 20A, IP MOTORIZED


SPARE BREAKERS AND (6) 20A, IP NON-MOTORIZED SPACE BREAKERS

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions



Fronius Inverter



Fronius Array Configuration Tool

Developing a Sustainable Photovoltaic Panel System

Choosing a PV System

- Uni-Solar PVL-144 Panel
 - “Peel-and-stick” technology
 - Minimal installation required
 - No additional structural design considerations
- Fronius IG Plus 10.0-1 Inverter
 - Max 11.5kW power
- Creating the array
 - Configuration Tool – 10 modules x 8 strings = 11.5kW




Installation of Uni-Solar panels

Developing a Sustainable Photovoltaic Panel System

Placing the Array

- Optimal solar gains along west portion of roof
- Minimal shadows from rooftop mechanical units



Aerial view of roof with solar panel placement

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions

Inverter Estimate		
(1) Fronius IG Plus 10.0-1 Inverter	(80) Uni-Solar PVL-144 Panels	Total
\$6,796	\$64,000	70,796.00

Developing a Sustainable Photovoltaic Panel System

Cost Impact

- Total cost of materials for system: **\$70,796**
 - Does not include installation costs

Payback Period

- PV Watts by National Renewable Energy Labs
- Payback period: **49 years**

Station Identification		Results			
City:	Williamsport	Month	Solar Radiation (kWh/m ² -day)	AC Energy (kWh)	Energy Value (\$)
State:	Pennsylvania	1	3.00	1025	98.40
Latitude:	41.27° N	2	3.58	1084	104.06
Longitude:	77.05° W	3	4.50	1454	139.58
Elevation:	243 m	4	4.65	1391	133.54
PV System Specifications		5	5.23	1565	150.24
DC Rating:	11.0 kW	6	5.39	1530	146.88
DC to AC Derate Factor:	0.950	7	5.47	1573	151.01
AC Rating:	10.4 kW	8	5.25	1519	145.82
Array Type:	Fixed Tilt	9	4.62	1348	129.41
Array Tilt:	38.5°	10	3.75	1145	109.92
Array Azimuth:	180.0°	11	2.55	777	74.59
Energy Specifications		12	2.31	751	72.10
Cost of Electricity:	9.6¢/kWh	Year	4.20	15163	1455.65

PV Watts output data screen

Initial (Life-Cycle) Cost of System	Energy Savings per Year	Payback Period
\$70,796	\$1,455.64	49 Years

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- **Electrical Breadth**
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions

Recommendations

- Sustainable systems are important for our environment
- Geisinger should consider a PV system
- **The proposed system's payback period is too long**



Typical PV panel array

Estimating Cost Using Building Information Modeling

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions

ANALYSIS 3

Estimating Cost Using Building Information Modeling

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions



Estimating Cost Using Building Information Modeling

Background

- No model was provided prior to estimating
- Three significant hand estimates were performed
 - Total time spent: 43 days

Critical Industry Issue

- PACE Seminar: *“How can BIM be used in estimating?”*
- Implementing BIM into the CM estimating process

Preconstruction		278	10-Dec-07	31-Dec-08
A1090	Sitework Schematic Design	54	10-Dec-07	21-Feb-08
A1100	Building Schematic Design	45	14-Jan-08	14-Mar-08
A1110	CM Kickoff Meeting	0	17-Jan-08	
A1120	Sitework Land Development Preparation	40	14-Feb-08	09-Apr-08
A1130	Building Schematic Design Dwg. Issued	0		04-Apr-08
A1140	Schematic Design Estimate	14	07-Apr-08	24-Apr-08
A1150	Building Design Development	23	23-Apr-08	23-May-08
A1160	Issue CD Drawings - Structural Steel	0	16-May-08	
A1170	Steel Contractor Procurement	25	16-May-08	19-Jun-08
A1180	Sitework Construction Documents	30	16-May-08	26-Jun-08
A1190	Issue Building DD Drawings	0	20-May-08	
A1200	Design Development Estimate	15	30-May-08	19-Jun-08
A1210	Issue CD Drawings - Site	0	13-Jun-08	
A1220	Sitework Contractor Procurement	20	13-Jun-08	10-Jul-08
A1230	Building Construction Documents	33	18-Jun-08	01-Aug-08
A1240	Issue CD Drawings - Building	0	05-Aug-08	
A1250	Develop Control Budget / Bidding	35	05-Aug-08	22-Sep-08
A1260	Addition Construction Documents	15	03-Oct-08	23-Oct-08
A1270	Addition Steel Drawings	15	03-Oct-08	23-Oct-08
A1280	Negotiate Addition Change Orders	30	20-Nov-08	31-Dec-08

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions

Objective

- Compare traditional estimating methods against BIM estimating methods for accuracy and efficiency in the structural system estimate.

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using

BIM

- Conclusions
- Questions

Estimating Cost Using Building Information Modeling

Traditional Estimate


- Taken off with ruler and scale
- Accurate to only nearest foot due to quality of drawings
- Prices generated from *RS Means*
- Estimated Cost: **\$1,166,098**
- Total estimate time: **6 hours**

Structural Steel System Estimate Comparison - Hand Estimate					
Item	Unit Cost	Actual Cost	Estimated Cost	Difference	% Difference
Steel System	3,325.41/TON	\$1,335,233	\$1,166,098	-\$169,135	-12.67



Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions




Creating a Quantity Schedule in Revit

Estimating Cost Using Building Information Modeling

Revit Quantity Schedules Estimate

- Created a schedule in Revit
- Sorted columns and beams by size and length
- Exported spreadsheet to Microsoft Excel
- Estimated Cost: **\$1,166,129**
- Total estimate time: **45 minutes**

Structural Steel System Estimate Comparison - Revit Estimate					
Item	Unit Cost	Actual Cost	Estimated Cost	Difference	% Difference
Steel System	\$3,324.38/TON	\$1,335,233	\$1,166,129	-\$169,104	-12.66



Creating a Quantity Schedule in Revit

Outline


- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- **Cost Estimating Using BIM**
- Conclusions
- Questions



Estimating Cost Using Building Information Modeling

Autodesk Quantity Takeoff Estimate

- Exported Revit structural model to DWFs
- Opened DWF in QTO
- Extremely easy to visualize the takeoff
- Additional time for software instruction and installation
- Identical quantities as Revit Quantity Schedule
- Total estimate time: **5.5 hours**



Exporting Structural Revit Model to QTO


Estimating Cost Using Building Information Modeling

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions

Comparison of Methods

- Revit Quantity Schedule was the fastest method
- QTO only took 30 minutes after training
- All methods were within 0.01% of each other
 - May not apply for more complex estimates (curved surfaces)
- Currently BIM takeoffs are only used as verification
 - Have potential to soon be trusted as alternative method
- Large savings in project schedule
 - Can accelerate the preconstruction phase



Bar chart showing time spent on each estimate

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- **Conclusions**
- Questions

Conclusions

Conclusions

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- **Conclusions**
- Questions

Pre-Cast Concrete Façade

- Good architectural substitute
- Substantial cost and schedule savings
- **Revit used to generate total SF of curtain wall**



Conclusions

Sustainable Photovoltaic Panel System

- Important to consider sustainability in construction practices
- Initial design to use “peel-and-stick” PV panel system
- Quantify the energy return – Site lighting
- Re-evaluate sustainable PV system for faster ROI
- **Revit used to perform solar shading studies for maximum sun exposure**



Estimating Using BIM

- Critical Industry Issue – “*How do we use BIM for estimating?*”
- Faster, more accurate estimates
- QTO allows for more detailed, complex schedules
- Transition to automated takeoffs is the future
- **Revit and QTO used to perform quantity estimates**



The Future of Building Information Modeling

- BIM technology becoming a new industry standard
 - LEED, 3D MEP Coordination, Electronic Document Sharing
 - Becoming more accepted by subcontractors

What does this mean for construction managers?

- More efficient projects
- More money and time saved

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- **Conclusions**
- Questions

Outline

- Project Overview
- Project Background
- Thesis Theme
- Architectural Breadth
 - Aluminum Panel vs. Pre-cast Concrete Facade
- Electrical Breadth
 - Solar Analysis
- Cost Estimating Using BIM
- Conclusions
- Questions

Questions

Questions?

Acknowledgements

Penn State University

Dr. Magent
Dr. Riley
Professor Holland

Alexander Building Construction

Stephen Wilt
Mike Stambaugh
Dave Carll
Tim Kay
Tina Petrie
Erica Craig

Geisinger Health System

High Concrete Group

Industry Professionals from the PACE Roundtable